


TP-Link 2.4GHz 300Mbps 9dBi Outdoor CPE 300 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link Product code: CPE210

Product name: 2.4GHz 300Mbps 9dBi Outdoor CPE







Features		Design	
2.4 GHz *	✓	Product colour *	White
5 GHz *	×	International Protection (IP) code	IPX5
Maximum data transfer rate *	300 Mbit/s	Reset button	✓
Maximum data transfer rate (2.4 GHz)	300 Mbit/s	LED indicators	1
Frequency band	2.4 - 2.483 GHz	Antenna	
Bandwidth	2.4 GHz	Antenna type *	Internal
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenna features Antennas quantity	Integrated antenna 1
MIMO	✓	Antenna gain level (max)	9 dBi
MIMO type	Multi User MIMO	Performance	
Maximum outdoor range	5000 m	Built-in processor	✓
Receiver sensitivity	802.11b: 11M: -95dBm, 5.5M: -96dBm, 2M: -96dBm, 1M: -96dBm 1M: -96dBm 2802.11g: 54M: -79dBm, 48M: -80dBm, 36M: -84dBm, 6-24M: -88dBm 802.11n: MCS15: -76dBm, MCS14: -78dBm, MCS13: -80dBm, MCS12: -84dBm, MCS11: -87dBm, MCS10: -91dBm, MCS9: -93dBm, MCS8: -96dBm, MCS7: -76dBm, MCS6: -78dBm, MCS5: -80dBm, MCS4: -84dBm, MCS3: -87dBm, MCS2: -91dBm, MCS1: -93dBm, MCS0: -96dBm	Certification	Qualcomm Atheros 560 MHz 8 MB 64 MB Microsoft Windows 98SE, NT, 2000, XP, Vista or Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux. CC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-ark - RoHS, IPX5
Security		Weight & dimensions	
Security algorithms *	64-bit WEP, 128-bit WEP, 152-bit WEP, SSID, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK	Width Depth Height	224 mm 79 mm 60 mm
MAC address filtering	✓	Packaging content	
Protocols		Cables included	AC
Management protocols	TDMA	Mounting kit	✓
Management features		Operational conditions	
Web-based management Management platform	✓ Pharos Control	Operating relative humidity (H-H) Operating temperature (T-T) Storage temperature (T-T)	10 - 90% -30 - 70 °C -40 - 70 °C

Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	1	Storage relative humidity (H-H)	5 - 95%
Power		Logistics data	
Power over Ethernet (PoE) *	✓	Harmonized System (HS) code	85176990
AC input voltage	100 - 240 V		
AC input frequency	50 - 60 Hz		
Input current	0.8 A		
Output voltage	24 V		
Output current	1 A		
Power consumption (max)	10.5 W		
Design			
Placement *	Wall		

