



TP-Link EAP245 traadita kohtvõrgu pääsupunkt 1300 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link

Product code: EAP245

Product name : EAP245

TP-Link EAP245. 2,4 GHz, 5 GHz, Andmete edastamise maksimaalne määr: 1300 Mbit/s. Turvaalgoritmid: 64-bit WEP, 128-bit WEP, 152-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge



Funktsioonid		Võimsus	
2,4 GHz *	✓	AC-sisendpinge	12 V
5 GHz *	✓	Sisendvool	1.5 A
Andmete edastamise maksimaalne määr *	1300 Mbit/s	Võimsustarve (tüüpiline)	12,3 W
Maksimaalne andmeedastuskiirus (2.4 GHz)	450 Mbit/s	Disain	
Maksimaalne andmeedastuskiirus (5 GHz)	1300 Mbit/s	Paigutus *	Lagi, Sein
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s	Toote värv *	Valge
Sagedusriba	2.4, 5 GHz	Kaabli luku pesa	✓
Võrgustandardid	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af	Kaabli luku pesa tüüp	Kensington
Automaatne kanalivalik	✓	Lähtestusnupp	✓
MIMO	✓	LED-indikaatorid	Võimsus
MIMO tüüp	Multi User MIMO	Sertifikaat	CE, FCC, RoHS
Virtuaalse LANi elemendid	SSID-based VLAN assignment	Antenn	
Kiiruse piiramine	✓	Antenni tüüp *	Sisemodem
Juhtmevaba isolatsioon	✓	Antenni suuna tüüp	Mitmesuunaline
Airtime Fairness (ATF)	✓	Antenni elemendid	Integreeritud antenn
Teenusekvaliteedi (QoS) tugi	✓	Antennivõimenduse tase (maksimaalne)	4 dBi
Jõuülekanne	27 dBmW	Toimimine	
Turvalisus		Ühilduvad operatsioonisüsteemid	Microsoft Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10
Turvaalgoritmid *	64-bit WEP, 128-bit WEP, 152-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Kaal ja mõõtmed	
MAC-aadresside filtreerimine	✓	Laius	205,4 mm
SSID-tugede arv	16	Sügavus	181,6 mm
Pordipõhine võrgu juurdepääsukontroll (PNAC)	✓	Kõrgus	37,4 mm
Pääsuloend (ACL)	✓	Pakendi sisu	
Juhtimisfunktsioonid		Koos PoE adapteriga	✓
Veebipõhine haldus	✓	Paigalduskomplekt	✓
		Kiirstardi juhend	✓

Juhtimisfunktsioonid		Töötingimused	
Logiserver	✓	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Pesad & liidesed		Kasutamistemperatuur (T-T)	0 - 40 °C
Ethernet LAN (RJ-45) pordid *	2	Hoiustamistemperatuur (T-T)	-40 - 70 °C
DC-pistik	✓	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Võimsus		Logistika andmed	
Power over Ethernet tugi *	✓	Harmonized System (HS) kood	85176990



5715063435403

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-AUG-2024. Prints or copies of Information are only valid on the printed Publication date