



## TP-Link Archer T2U Nano 433 Mbit/s

**Brand :** TP-Link

**Product code:** ARCHER T2U NANO V1

**Product name :** Archer T2U Nano

TP-Link Archer T2U Nano. Ühenduvustehnoloogia: Juhtmevaba, Hostiliides: USB. Andmete edastamise maksimaalne määr: 433 Mbit/s, Wi-Fi standard: Wi-Fi 5 (802.11ac), Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz). Toide USB kaudu. Toote värv: Must



Pesad & liidesed		Võimsus	
Ühenduvustehnoloogia *	Juhtmevaba	Toide USB kaudu	✓
Hostiliides *	USB	<b>Süsteeminõuded</b>	
USB versioon	2.0	Toetatud Windowsi operatsioonisüsteemid	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows XP
<b>Võrgustumine</b>		Toetatud Maci operatsioonisüsteemid	macOS
Andmete edastamise maksimaalne määr *	433 Mbit/s	Toetatud Linuxi operatsioonisüsteemid	✓
Võrgustandardid *	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x	<b>Töötingimused</b>	
WiFi	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Wi-Fi laineala	Kaks sagedusala (2,4 GHz / 5 GHz)	Hoiustamistemperatuur (T-T)	-40 - 70 °C
Sagedusvahemik	2,4 - 5 GHz	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Wi-Fi standard	Wi-Fi 5 (802.11ac)	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
WiFi-standardid	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	<b>Kaal ja mõõtmed</b>	
Toetatud WLAN andmeedastuskiirused	11,54,150,200,433 Mbit/s	Laius	15 mm
Modulatsioon	16-QAM, 64-QAM, 256-QAM, CCK, COFDM, DBPSK, DQPSK, OFDM	Sügavus	7,1 mm
Turvaalgoritmid	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK	Kõrgus	18,6 mm
Ribalaius (esimene)	2,4 GHz	<b>Pakendi andmed</b>	
Ribalaius (teine)	5 GHz	Kogus	1
<b>Disain</b>		Pakendi laius	138 mm
Toote värv	Must	Pakendi sügavus	128 mm
Sisemine *	✗	Pakendi kõrgus	30 mm
Antenn	✓	Pakendi kaal	90 g
Antenni kujundus	Sisemodem	<b>Pakendi sisu</b>	
Antenni suuna tüüp	Mitmesuunaline	Kiirpaigaldusjuhend	✓

Disain	Tehnilised andmed	
Vastuvõtja tundlikkus	5GHz □ 11a 6Mbps: -90dBm 11a 54Mbps: -73dBm 11n HT20 MCS0: -89dBm 11n HT20 MCS7: -70dBm 11n HT40 MCS0: -86dBm 11n HT40 MCS7: -67dBm 11ac VHT80 MCS0: -82dBm 11ac VHT80 MCS9: -56dBm 2.4GHz: 11b 1Mbps: -96dBm 11b 11Mbps: -88dBm 11g 6Mbps: -89dBm 11g 54Mbps: -74dBm 11n HT20 MCS0: -89dBm 11n HT20 MCS7: -72dBm 11n HT40 MCS0: -86dBm 11n HT40 MCS7: -66dBm	Vastavussertifikaadid RoHS
Sertifikaat	CE, FCC	<b>Muud funktsioonid</b>
		Edastuse võimsusaste 20 - 20 dBmW



6935364082635



0840030700019



840030700019

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.