



## TP-Link RE305 võrgulaiendaja Võrguvõimendi Valge 10, 100 Mbit/s

Brand : TP-Link

Product code: RE305

Product name : RE305

TP-Link RE305. Tüüp: Võrguvõimendi, Andmeedastuskiirus: 867 Mbit/s, Ethernet LAN-i andmeedastuskiirused: 10,100 Mbit/s. Antenni tüüp: Sisemodem, Saatja võimsus (CE): 17 dbm. Kaabeldustehnoloogia: 10/100Base-T(X), Võrgustandardid: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u, WiFi-standardid: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac). Toote värv: Valge, Kogus pakis: 1 tk, Päritoluriik: Hiina. AC-sisendpinge: 220 - 240 V, AC-sisendsagedus: 60 Hz, Elektritarbimine (max): 7,3 W



Toimimine		Disain	
Tüüp *	Võrguvõimendi	Kogus pakis	1 tk
Andmeedastuskiirus	867 Mbit/s	Päritoluriik	Hiina
Ethernet LAN-i andmeedastuskiirused	10,100 Mbit/s	Lähtestusnupp	✓
WPS-nupp	✓	<b>Võimsus</b>	
Toetatud Windowsi operatsioonisüsteemid	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows XP	AC-sisendpinge	220 - 240 V
Mac-ühilduvus	✓	AC-sisendsagedus	60 Hz
Toetatud Maci operatsioonisüsteemid	✓	Elektritarbimine (max)	7,3 W
Toetatud Linuxi operatsioonisüsteemid	✓	Pistiku tüüp	Tüüp I
<b>Antenn</b>		<b>Töötingimused</b>	
Antennide arv	2	Kasutamistemperatuur (T-T)	0 - 40 °C
Antenni tüüp	Sisemodem	Hoiustamistemperatuur (T-T)	-40 - 70 °C
Saatja võimsus (CE)	17 dbm	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
<b>Võrgustumine</b>		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Kaabeldustehnoloogia	10/100Base-T(X)	<b>Kaal ja mõõtmed</b>	
Võrgustandardid	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u	Laius	80 mm
WiFi	✓	Sügavus	78 mm
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Kõrgus	77 mm
WiFi andmeedastuskiirus (maksimaalne)	867 Mbit/s	<b>Tehnilised andmed</b>	
Wi-Fi laineala	Kaks sagedusala (2,4 GHz / 5 GHz)	Vastavussertifikaadid	CE, Föderaalne kommunikatsioonikomisjon (FCC), RoHS
Turvaalgoritmid	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK	<b>Pakendi sisu</b>	
<b>Pesad &amp; liidesed</b>		Kiirstardi juhend	✓
Ethernet LAN (RJ-45) pordid	1	<b>Pakendi andmed</b>	
<b>Disain</b>		Pakendi tüüp	Karp
Toote värv	Valge	Pakendi laius	150 mm
LED-indikaatorid	✓	Pakendi sügavus	160 mm
		Pakendi kõrgus	200 mm
		Pakendi kaal	300 g

**Logistika andmed**

Harmonized System (HS) kood 85176990



6935364097974

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date