



## TP-Link TL-SG108PE võrgulüliti Juhitav L2 Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product code: TL-SG108PE

Product name : TL-SG108PE



TP-Link TL-SG108PE. Lüliti tüüp: Juhitav, Lüliti kiht: L2. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 8. MAC-aadresside tabel: 4000 sisestust, Lülitusvõime: 16 Gbit/s. Võrgustandardid: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Power over Ethernet tugi



Juhtimisfunktsioonid		Disain	
Lüliti tüüp *	Juhitav	Sertifikaat	FCC, CE, RoHS
Lüliti kiht	L2	<b>Võimsus</b>	
<b>Pesad &amp; liidesed</b>		Kaasas toiteplokk *	✓
RJ-45 Etherneti ühenduse pesade arv *	8	AC-sisendpinge	220 V
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	AC-sisendsagedus	50 Hz
<b>Võrgustumine</b>		Sisendvool	1.25 A
Võrgustandardid *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Elektritarbimine (max)	65,2 W
10G-tugi *	✗	<b>Internet elektrivõrgu kaudu (PoE)</b>	
Pordipeegeldus	✓	Power over Ethernet tugi *	✓
Linkide koondamine	✓	Toide üle võrgu (PoE) pesade arv	4
Levindamise tormi kontroll	✓	Toide üle võrgu (PoE) pesade arv	4
Kiiruse piiramine	✓	Toide üle võrgu (PoE) võimsusühikuid kokku	55 W
VLAN-i tugi	✓	<b>Töötingimused</b>	
VLAN-ide arv	32	Kasutamistemperatuur (T-T)	0 - 40 °C
<b>Andmeedastus</b>		Hoiustamistemperatuur (T-T)	-40 - 70 °C
Lülitusvõime *	16 Gbit/s	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
MAC-aadresside tabel *	4000 sisestust	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 95 protsenti
Ladusta-ja-edasta	✓	<b>Kaal ja mõõtmed</b>	
Hiielkaadrite tugi	✓	Laius	158 mm
Hiielkaadrite	15000	Sügavus	101 mm
Andmesidepaketi edastamise kiirus (1 Gbit/s)	11900000 pps	Kõrgus	25 mm
Paketi puhvermälu	1,5 MB	<b>Pakendi andmed</b>	
<b>Turvalisus</b>		Kaablid kaasa arvatud	Vahelduvvool
IGMP-jälgimine	✓	Kasutusjuhend	✓
Tsükli kaitse	✓	Pakendi tüüp	Karp
<b>Disain</b>		<b>Logistika andmed</b>	
Püstikmontaaž *	✗	Harmonized System (HS) kood	85176990

## Disain

Toote värv

Must

LED-indikaatorid

Tegevus, Link, Internet elektrivõrgu  
kaudu (PoE), Võimsus, Kiirus,  
Staatus



5054242560797

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date