



## TP-Link TL-SF1005P võrgulüliti Mittejuhitav Fast Ethernet (10/100) Power over Ethernet tugi Must

**Brand :** TP-Link

**Product code:** TL-SF1005P

**Product name :** TL-SF1005P

TP-Link TL-SF1005P. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Fast Ethernet (10/100), RJ-45 Etherneti ühenduse pesade arv: 5. Täisdupleks. MAC-aadresside tabel: 2000 sisestust, Lülitusvõime: 1 Gbit/s. Võrgustandardid: IEEE 802.3af, IEEE 802.3x. Power over Ethernet tugi



| Juhtimisfunktsioonid                     |                           | Disain                                     |                   |
|------------------------------------------|---------------------------|--------------------------------------------|-------------------|
| Lüliti tüüp *                            | Mittejuhitav              | LED-indikaatorid                           | ✓                 |
| Pesad & liidesed                         |                           | Sertifikaat                                | FCC, CE, RoHS     |
| RJ-45 Etherneti ühenduse pesade arv *    | 5                         | Võimsus                                    |                   |
| RJ-45 Etherneti ühenduse pesade tüüp *   | Fast Ethernet (10/100)    | Kaasas toiteplokk *                        | ✓                 |
| Võrgustumine                             |                           | Elektritarbimine (max)                     | 63,51 W           |
| Võrgustandardid *                        | IEEE 802.3af, IEEE 802.3x | Internet elektrivõrgu kaudu (PoE)          |                   |
| 10G-tugi *                               | ✗                         | Power over Ethernet tugi *                 | ✓                 |
| Etherneti vaskaablite tehnoloogia        | 10BASE-T, 100BASE-TX      | Toide üle võrgu (PoE) pesade arv           | 4                 |
| Toetatud kaablitüübid                    | Cat3, Cat4, Cat5, Cat5e   | Toide üle võrgu (PoE) võimsusühikuid kokku | 58 W              |
| Täisdupleks                              | ✓                         | Töötingimused                              |                   |
| Voo reguleerimise tugi                   | ✓                         | Kasutamistemperatuur (T-T)                 | 0 - 40 °C         |
| Auto MDI/MDI-X                           | ✓                         | Hoiustamistemperatuur (T-T)                | -40 - 70 °C       |
| Automaatne ühildumine                    | ✓                         | Suhteline õhuniiskus kasutamisel (H-H)     | 10 - 90 protsenti |
| Automaatse MAC-aadressi tuvastamise tugi | ✓                         | Suhteline õhuniiskus (H-H) hoiustamisel    | 5 - 90 protsenti  |
| Automaatse MAC-aadressi aegumise tugi    | ✓                         | Soojuse hajumine                           | 5,73 BTU/h        |
| Andmeedastus                             |                           | Kaal ja mõõtmed                            |                   |
| Lülitusvõime *                           | 1 Gbit/s                  | Laius                                      | 99,8 mm           |
| MAC-aadresside tabel *                   | 2000 sisestust            | Sügavus                                    | 98 mm             |
| Ladusta-ja-edasta                        | ✓                         | Kõrgus                                     | 25 mm             |
| Disain                                   |                           | Pakendi andmed                             |                   |
| Püstikmontaaž *                          | ✗                         | Kasutusjuhend                              | ✓                 |
| Toote värv                               | Must                      | Pakendi tüüp                               | Karp              |
|                                          |                           | Logistika andmed                           |                   |
|                                          |                           | Harmonized System (HS) kood                | 85176990          |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date