



## TP-Link TL-SF1008P võrgulüli Mittejuhitav Fast Ethernet (10/100) Power over Ethernet tugi Oliiv

Brand : TP-Link

Product code: TL-SF1008P

Product name : TL-SF1008P



TP-Link TL-SF1008P. Lüli tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Fast Ethernet (10/100), RJ-45 Etherneti ühenduse pesade arv: 8. Täisdupleks. MAC-aadresside tabel: 2000 sisestust, Lülitusvõime: 1,6 Gbit/s. Võrgustandardid: IEEE 802.1Qbb. Alalisvoolu sisendpinge: 48 V. Toitepistik: Alaldi sisendi pesa. Power over Ethernet tugi



Juhtimisfunktsioonid		Disain	
Lüli tüüp *	Mittejuhitav	Püstikmontaaž *	✗
<b>Pesad &amp; liidesed</b>		Toote värv	Oliiv
RJ-45 Etherneti ühenduse pesade arv *	8	LED-indikaatorid	✓
RJ-45 Etherneti ühenduse pesade tüüp *	Fast Ethernet (10/100)	Sertifikaat	FCC, CE, RoHS
Toitepistik	Alaldi sisendi pesa	<b>Toimimine</b>	
<b>Võrgustumine</b>		Laiendusmoduli tugi	✓
Võrgustandardid *	IEEE 802.1Qbb	Sisesehitatud protsessor	✓
10G-tugi *	✗	Protsessori tootja	Broadcom
Täisdupleks	✓	Mälu tüüp	DRAM
Voo reguleerimise tugi	✓	<b>Võimsus</b>	
Auto MDI/MDI-X	✓	Alalisvoolu sisendpinge	48 V
Ethernet LAN-i andmeedastuskiirused	100 Mbit/s	<b>Internet elektrivõrgu kaudu (PoE)</b>	
Automaatse MAC-aadressi tuvastamise tugi	✓	Power over Ethernet tugi *	✓
Automaatse MAC-aadressi aegumise tugi	✓	Toide üle võrgu (PoE) pesade arv	4
<b>Valgusjuhe</b>		Toide üle võrgu (PoE) võimsusühikuid kokku	60,2 W
Etherneti kiudkaablite tehnoloogia	40GBASE-SR4	<b>Töötingimused</b>	
<b>Andmeedastus</b>		Kasutamistemperatuur (T-T)	0 - 40 °C
Lülitusvõime *	1,6 Gbit/s	Hoiustamistemperatuur (T-T)	-40 - 70 °C
MAC-aadresside tabel *	2000 sisestust	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Ladusta-ja-edasta	✓	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
<b>Turvalisus</b>		<b>Kaal ja mõõtmed</b>	
DHCP elemendid	DHCPv6 relay	Laius	171 mm
Pääsuloend (ACL)	✓	Sügavus	98 mm
<b>Protokollid</b>		Kõrgus	27 mm
GARP VLAN Registration Protocol (GVRP)	✓	<b>Pakendi andmed</b>	
		Kasutusjuhend	✓
		Pakendi tüüp	Karp

Protokollid		Logistika andmed	
Marsruutimisprotokollid	OSPF	Harmonized System (HS) kood	85176990
IPv4 ja IPv6 elemendid	IPv6 portal		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date