



TP-Link CPE710 traadita kohtvõrgu pääsupunkt 867 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link

Product code: CPE710

Product name : CPE710

TP-Link CPE710. 5 GHz, Andmete edastamise maksimaalne määr: 867 Mbit/s. Turvaalgoritmid: HTTPS, SNMP, SSH, WPA, WPA2, WPA2-AES, WPA2-PSK, WPA2-TKIP. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge



Features		Design	
2.4 GHz *	✗	Product colour *	White
5 GHz *	✓	Housing material	Plastic
Maximum data transfer rate *	867 Mbit/s	International Protection (IP) code	IP65
Ethernet LAN data rates	10,100,1000 Mbit/s	Reset button	✓
Frequency band	5.15 - 5.85 GHz	LED indicators	Power
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11n	Antenna	
Channel bandwidth	80 MHz	Antenna gain level (max)	23 dBi
Automatic channel selection	✓	Performance	
MIMO	✓	Built-in processor	✓
Wireless isolation	✓	Processor frequency	750 MHz
Dynamic Frequency Selection (DFS)	✓	Flash memory	16 MB
Transmitting power	27 dBmW	Internal memory	128 MB
Security		Compatible operating systems	Microsoft Windows 98SE, NT, 2000, XP, Vista, Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX, Linux
Security algorithms *	HTTPS, SNMP, SSH, WPA, WPA2, WPA2-AES, WPA2-PSK, WPA2-TKIP	Certificates	
MAC address filtering	✓	Certification	CE, FCC, RoHS, IC
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast, SSID broadcast on/off	Weight & dimensions	
IGMP snooping	✓	Width	366 mm
Auto Wireless Distribution System (WDS)	✓	Depth	280 mm
Protocols		Height	207 mm
Universal Plug and Play (UPnP)	✓	Packaging data	
Management features		Package type	Box
Web-based management	✓	Packaging content	
Syslog	✓	PoE adapter included	✓

Ports & interfaces		Packaging content	
Ethernet LAN (RJ-45) ports *	1	Cables included	AC
Power		Quick start guide	✓
Power over Ethernet (PoE) *	✓	Operational conditions	
AC input voltage	100 - 240 V	Operating relative humidity (H-H)	10 - 90%
AC input frequency	50 - 60 Hz	Operating temperature (T-T)	-40 - 70 °C
Output voltage	24 V	Storage temperature (T-T)	-40 - 70 °C
Output current	0.6 A	Storage relative humidity (H-H)	5 - 95%
Design		Logistics data	
Placement *	Pole	Harmonized System (HS) code	85176990



6935364053345



6935364089702



0845973089702



845973089702

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.