tp-link

TP-Link Deco S4 (3-pack) Kaks sagedusala (2,4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) Valge 2 Sisemodem

Brand : TP-Link
Product code: DECO S4(3-PACK)

Product name : Deco S4 (3-pack)

TP-Link Deco S4 (3-pack). Toote värv: Valge, Antenni tüüp: Sisemodem, Toote tüüp: Võrgusüsteem. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN edastuskiirus (max): 1167 Mbit/s. Tulemüür: SPI Firewall, Toetatud mobiilsed operatsioonisüsteemid: Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2,.... AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 50 - 60 Hz, AC-adapteri väljundpinge: 12 V. Vastavussertifikaadid: CE, RoHS, Sertifikaat: FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC

Design

Product type	Mesh system
Product colour *	White
LED indicators	Power
Antenna type *	Internal
Antennas quantity	2
Maximum coverage	370 m²
Reset button	✔

Wireless LAN features

Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rate (max) *	1167 Mbit/s
WLAN data transfer rate (first band)	300 Mbit/s
WLAN data transfer rate (second band)	867 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA, WPA2
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Dynamic IP	✔
Static IP	✔
Dynamic DNS (DDNS)	✔
Guest access	✔

Features

Features

Parental control	✔
MU-MIMO technology	✔
MIMO	✔

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2
DC-in jack	✔

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
AC adapter output voltage	12 V
AC adapter output current	1.5 A

Certificates

Compliance certificates	CE, RoHS
Certification	FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC

Sustainability

Sustainability compliance	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	90.7 mm
Depth	90.7 mm
Height	162.3 mm

Features

Band steering	✔
Quality of Service (QoS) support	✔
Port forwarding	✔
Firewall security	SPI Firewall
BeamForming	✔
DHCP client	✔
DHCP server	✔
Mobile operating systems supported	Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3

Weight & dimensions

Weight	1.1 kg

Packaging content

Number of products included	3 pc(s)
AC adapter included	✔
Number of units included	3 pc(s)
Ethernet cable	✔

Packaging data

Package width	348 mm
Package depth	213 mm
Package height	160 mm
Package weight	1.76 kg

6935364089726