



TP-Link Archer AX1500 juhtmevaba ruuter Gigabit Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Must

Brand : TP-Link

Product code: ARCHER AX1500

Product name : Archer AX1500

TP-Link Archer AX1500. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN edastuskiirus (max): 1201 Mbit/s. Ethernet LAN-liidese tüüp: Gigabit Ethernet, VPN-server: OpenVPN, PPTP. Turvaalgoritmid: WEP, WPA, WPA2. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Must. Kaablid kaasa arvatud: Vahelduvvool, LAN (RJ-45)



WAN-ühendus		Turvalisus	
Ethernet WAN *	✓	Vanemlik kontroll	✓
DSL WAN *	✗	URL-i filtreerimine	✓
SIM kaardi ava *	✗	DMZ-tugi	✓
3G/4G USB modemi ühilduvus *	✗	Protokollid	
Juhtmevaba LAN-i omadused		DHCP-klient	✓
Wi-Fi laineala *	Kaks sagedusala (2,4 GHz / 5 GHz)	DHCP-server	✓
Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Universaalne Plug and Play (UPnP)	✓
WLAN edastuskiirus (max) *	1201 Mbit/s	Disain	
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Toote värv	Must
WLAN edastuskiirus (esimene laineala)	1201 Mbit/s	Sisse/välja lülit	✓
WLAN edastuskiirus (teine laineala)	300 Mbit/s	Toote tüüp *	Laua peale asetatav ruuter
Võrgustumine		Pakendi sisu	
Ethernet LAN *	✓	Kaablid kaasa arvatud	Vahelduvvool, LAN (RJ-45)
Ethernet LAN-liidese tüüp *	Gigabit Ethernet	AC-adapter kaasa arvatud	✓
Portide suunamine	✓	Kiirpaigaldusjuhend	✓
Pordi aktiveerimine	✓	Antenn	
Dünaamiline DNS (DDNS)	✓	Antenni kujundus *	Väline
VPN-server	OpenVPN, PPTP	Antennide arv	4
Mobiilivõrk		Võimsus	
3G	✗	Toiteallika tüüp *	Vahelduvvool
4G	✗	Väljundpinge	12 V
Pesad & liidesed		Väljundvool	1 A
Ethernet LAN (RJ-45) pordid *	4	Töötingimused	
		Kasutamistemperatuur (T-T)	0 - 40 °C
		Hoiustamistemperatuur (T-T)	-40 - 70 °C

Juhtimisfunktsioonid		Töötingimused	
Lähtestusnupp	✓	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
WPS-nupp	✓	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Tehnoloogia MU-MIMO	✓		
Turvalisus		Kaal ja mõõtmed	
Turvaalgoritmid	WEP, WPA, WPA2	Laius	260,2 mm
Tulemüür	✓	Sügavus	135 mm
Pääsuloend (ACL)	✓	Kõrgus	38,6 mm



6935364085193

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.