



TP-Link Archer C54 juhtmevaba ruuter Kiire Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Must

Brand : TP-Link

Product code: ARCHER C54

Product name : Archer C54

TP-Link Archer C54. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN edastuskiirus (max): 867 Mbit/s. Ethernet LAN-liidese tüüp: Kiire Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100 Mbit/s, Võrgustandardid: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11d, IEEE 802.11g, IEEE 802.11n. Turvaalgoritmid: WEP, WPA, WPA2, WPA2-Enterprise. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Must. Antenni kujundus: Väline



WAN-ühendus		Turvalisus	
Ethernet WAN *	✓	Turvaalgoritmid	WEP, WPA, WPA2, WPA2-Enterprise
DSL WAN *	✓	Tulemüür	✓
SIM kaardi ava *	✗	Pääsuloend (ACL)	✓
Juhtmevaba LAN-i omadused		Stateful Packet Inspection (SPI)	✓
Wi-Fi laineala *	Kaks sagedusala (2,4 GHz / 5 GHz)	DMZ-tugi	✓
Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Protokollid	
WLAN edastuskiirus (max) *	867 Mbit/s	DHCP-klient	✓
WLAN edastuskiirus (esimene laineala)	867 Mbit/s	DHCP-server	✓
WLAN edastuskiirus (teine laineala)	300 Mbit/s	Universaalne Plug and Play (UPnP)	✓
Võrgustumine		Disain	
Ethernet LAN *	✓	Toote värv	Must
Ethernet LAN-liidese tüüp *	Kiire Ethernet	Toote tüüp *	Laua peale asetatav ruuter
Ethernet LAN-i andmeedastuskiirused	10,100 Mbit/s	Antenn	
Võrgustandardid	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11d, IEEE 802.11g, IEEE 802.11n	Antenni kujundus *	Väline
Portide suunamine	✓	Antennide arv	4
Pordi aktiveerimine	✓	Võimsus	
Dünaamiline DNS (DDNS)	✓	Toiteallika tüüp *	Vahelduvvool
Mobiilivõrk		Väljundpinge	9 V
3G	✗	Väljundvool	0,85 A
4G	✗	Töötingimused	
Pesad & liidesed		Kasutamistemperatuur (T-T)	0 - 40 °C
Ethernet LAN (RJ-45) pordid *	4	Hoiustamistemperatuur (T-T)	-40 - 60 °C
Juhtimisfunktsioonid		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Teenusekvaliteedi (QoS) tugi	✓	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Lähtestusnupp	✓	Kaal ja mõõtmed	
WPS-nupp	✓	Laius	115 mm
Tehnoloogia MU-MIMO	✓	Sügavus	106,7 mm
		Kõrgus	24,3 mm



6935364089337

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date