



TP-Link ARCHER C24 juhtmevaba ruuter Kiire Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Valge

Brand : TP-Link

Product code: ARCHER C24

Product name : ARCHER C24

TP-Link ARCHER C24. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN edastuskiirus (max): 433 Mbit/s. Ethernet LAN-liidese tüüp: Kiire Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100 Mbit/s, Võrgustandardid: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Turvaalgoritmid: WEP, WPA, WPA2. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Valge. Kaablid kaasa arvatud: LAN (RJ-45)



WAN-ühendus		Protokollid	
Ethernet WAN *	✓	DHCP-klient	✓
DSL WAN *	✗	DHCP-server	✓
SIM kaardi ava *	✗		
3G/4G USB modemi ühilduvus *	✗	Disain	
		Toote värv	Valge
Juhtmevaba LAN-i omadused		Toote tüüp *	Laua peale asetatav ruuter
Wi-Fi laineala *	Kaks sagedusala (2,4 GHz / 5 GHz)	Pakendi sisu	
Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Kaablid kaasa arvatud	LAN (RJ-45)
WLAN edastuskiirus (max) *	433 Mbit/s	AC-adapter kaasa arvatud	✓
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Kiirpaigaldusjuhend	✓
Võrgustumine		Jätkusuutlikkus	
Ethernet LAN *	✓	Jätkusuutlikkuse järgimine	✓
Ethernet LAN-liidese tüüp *	Kiire Ethernet	Antenn	
Ethernet LAN-i andmeedastuskiirused	10,100 Mbit/s	Antenni kujundus *	Väline
	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antennide arv	4
Mobiilivõrk		Funktsioonid	
3G	✗	Sisesehitatud protsessor	✓
4G	✗	Protsessorituumad	1
Pesad & liidesed		Võimsus	
Ethernet LAN (RJ-45) pordid *	5	Toiteallika tüüp *	Vahelduvvool
USB port *	✗	Väljundpinge	9 V
Mälukaardi pesa(d)	✗	Väljundvool	0,6 A
DC-pistik	✓	Töötingimused	
Juhtimisfunktsioonid		Kasutamistemperatuur (T-T)	0 - 40 °C
Teenusekvaliteedi (QoS) tugi	✓	Hoiustamistemperatuur (T-T)	-40 - 60 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti

Juhtimisfunktsioonid		Töötingimused	
Lähtestusnupp	✓	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
WPS-nupp	✓		
Turvalisus		Kaal ja mõõtmed	
Turvaalgoritmid	WEP, WPA, WPA2	Laius	115 mm
Tulemüür	✓	Sügavus	106,7 mm
Vanemlik kontroll	✓	Kõrgus	24,3 mm
URL-i filtreerimine	✓		
		Tehnilised andmed	
		Vastavussertifikaadid	RoHS



6935364089474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date