tp-link

TP-Link TL-SF1009P võrgulüliti Mittejuhitav Fast Ethernet (10/100) Power over Ethernet tugi Must

Brand : TP-Link

Product name : TL-SF1009P

Product code: TL-SF1009P

TP-Link TL-SF1009P. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Fast Ethernet (10/100), RJ-45 Etherneti ühenduse pesade arv: 9. Täisdupleks. MAC-aadresside tabel: 2000 sisestust, Lülitusvõime: 1,6 Gbit/s. Võrgustandardid: IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Alalisvoolu sisendpinge: 53.5 V. Toitepistmik: Alaldi sisendi pesa. Power over Ethernet tugi. Seinale kinnitatav

Management features	
Switch type *	Unmanaged

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	9
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)
Fast Ethernet (copper) ports quantity	9
Power connector	DC-in jack

Network	
Networking standards *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support *	✗
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Full duplex	✔
Half duplex	✔
Flow control support	✔
Auto MDI/MDI-X	✔
Auto-negotiation	✔
MAC address auto-learning supported	✔
MAC address auto-aging supported	✔

Data transmission	
Switching capacity *	1.6 Gbit/s
Forwarding rate	1.3392 Mpps
MAC address table *	2000 entries
Store-and-forward	✔

Power	
AC input voltage	220 V
AC input frequency	50 Hz
DC input voltage	53.5 V
Input current	1.31 A
Power consumption (max)	77.08 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Power over Ethernet plus (PoE+) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	65 W

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	262.84 BTU/h

Weight & dimensions	
Width	171 mm
Depth	98 mm
Height	27 mm

Packaging content	
User guide	✔

Packaging data	
AC adapter included	✔

Design

Rack mounting *	✘
Stackable *	✘
Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, PoE, Power
Wall mountable	✔

Performance

Fanless	✔

Power

Power source *	DC/PoE
Power supply included *	✘

Packaging data

Package type	Box
Package width	223 mm
Package depth	280 mm
Package height	68 mm
Package weight	980 g

Sustainability

Sustainability compliance	✔

Certificates

Compliance certificates	Federal Communications Commission (FCC), CE, RoHS
Certification	FCC, CE, RoHS

Logistics data

Harmonized System (HS) code	85176990

6935364052973

6935364052966

0845973099909

845973099909