



TP-Link TL-POE160S PoE-adapter Gigabit Ethernet

Brand : TP-Link

Product code: TL-POE160S

Product name : TL-POE160S

TP-Link TL-POE160S. Ethernet-liidese tüüp: Gigabit Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s, Kaabeldustehnoloogia: 10/100/1000. Toote värv: Must, Maksimaalne kasutuskaugus: 100 m, LED-indikaatorid: Võimsus. Väljundvõimsus: 30 W, AC-adaptori sisendpinge: 100 - 240 V, AC-adaptori sagedus: 50/60 Hz. Sertifikaat: FCC, CE, RoHS. Laius: 125 mm, Sügavus: 59,4 mm, Kõrgus: 36,8 mm



| | | | |
|-------------------------------|--|-----------------------------------|--|
| Network | | Operational conditions | |
| Ethernet interface type | Gigabit Ethernet | Operating relative humidity (H-H) | 10 - 90% |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Storage temperature (T-T) | -40 - 70 °C |
| Cabling technology | 10/100/1000 | Storage relative humidity (H-H) | 5 - 90% |
| Power over Ethernet (PoE) | ✓ | Weight & dimensions | |
| Networking standards | IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u | Width | 125 mm |
| Cable types supported | Cat3, Cat4, Cat5, Cat5e | Depth | 59.4 mm |
| Features | | Height | 36.8 mm |
| Product colour | Black | Packaging content | |
| Wall mountable | ✓ | Number of products included | 1 pc(s) |
| Plug and Play | ✓ | Wall mounting kit | ✓ |
| Maximum operating distance | 100 m | Power cord included | ✓ |
| LED indicators | Power | Quick installation guide | ✓ |
| Ports & interfaces | | Packaging content | TL-POE160S, power cord, RJ45 cable, installation guide, wall-mounting kits |
| Ethernet LAN (RJ-45) ports | 2 | Packaging data | |
| RJ-45 input ports | 1 | Package width | 170 mm |
| RJ-45 output ports | 1 | Package depth | 230 mm |
| Power | | Package height | 80 mm |
| Output power | 30 W | Package weight | 460 g |
| AC adapter input voltage | 100 - 240 V | Package type | Box |
| AC adapter frequency | 50/60 Hz | Logistics data | |
| Certificates | | Harmonized System (HS) code | 85044095 |
| Certification | FCC, CE, RoHS | | |
| Operational conditions | | | |
| Operating temperature (T-T) | 0 - 40 °C | | |



6935364073091



0845973072162



845973072162



6935364073084

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.