



# TP-Link TL-SG108-M2 võrgulüliti Mittejuhitav 2.5G Ethernet (100/1000/2500) Must

Brand : TP-Link

Product code: TL-SG108-M2

Product name : TL-SG108-M2



TP-Link TL-SG108-M2. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: 2.5G Ethernet (100/1000/2500), RJ-45 Etherneti ühenduse pesade arv: 8. MAC-aadresside tabel: 16000 sisestust, Lülitusvõime: 40 Gbit/s. Võrgustandardid: IEEE 802.3, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x. Seinale kinnitatav



| Juhtimisfunktsioonid                   |                                                                               | Toimimine                               |                           |
|----------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------|---------------------------|
| Lüliti tüüp *                          | Mittejuhitav                                                                  | Ilma ventilaatorita                     | ✓                         |
| Teenusekvaliteedi (QoS) tugi           | ✓                                                                             | Võimsus                                 |                           |
| Pesad & liidesed                       |                                                                               | Toiteallikas *                          | DC (alalisvool)           |
| RJ-45 Etherneti ühenduse pesade arv *  | 8                                                                             | Kaasas toiteplokk *                     | ✓                         |
| RJ-45 Etherneti ühenduse pesade tüüp * | 2.5G Ethernet (100/1000/2500)                                                 | Sisendvool                              | 1.5 A                     |
| 2.5G Etherneti (vask) portide arv      | 8                                                                             | Sisendpinge                             | 12 V                      |
| Võrgustumine                           |                                                                               | Internet elektrivõrgu kaudu (PoE)       |                           |
| Võrgustandardid *                      | IEEE 802.3, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x | Power over Ethernet tugi *              | ✗                         |
| 10G-tugi *                             | ✗                                                                             | Töötingimused                           |                           |
| Voo reguleerimise tugi                 | ✓                                                                             | Kasutamistemperatuur (T-T)              | 0 - 40 °C                 |
| Auto MDI/MDI-X                         | ✓                                                                             | Hoiustamistemperatuur (T-T)             | -40 - 70 °C               |
| Automaatne ühildumine                  | ✓                                                                             | Suhteline õhuniiskus kasutamisel (H-H)  | 10 - 90 protsenti         |
| Andmeedastus                           |                                                                               | Suhteline õhuniiskus (H-H) hoiustamisel | 5 - 90 protsenti          |
| Lülitusvõime *                         | 40 Gbit/s                                                                     | Soojuse hajumine                        | 53,4 BTU/h                |
| Edastamise kiirus                      | 29,8 Mpps                                                                     | Kaal ja mõõtmed                         |                           |
| MAC-aadresside tabel *                 | 16000 sisestust                                                               | Laius                                   | 226 mm                    |
| Ladusta-ja-edasta                      | ✓                                                                             | Sügavus                                 | 131 mm                    |
| Hiielkaadrite tugi                     | ✓                                                                             | Kõrgus                                  | 35 mm                     |
| Hiielkaadrite                          | 10000                                                                         | Pakendi andmed                          |                           |
| Paketi puhvermälu                      | 1,5 MB                                                                        | Kaablid kaasa arvatud                   | Vahelduvvool, LAN (RJ-45) |
| Disain                                 |                                                                               | Pakendi laius                           | 240 mm                    |
| Püstikmontaaž *                        | ✗                                                                             | Pakendi sügavus                         | 315 mm                    |
| Toote värv                             | Must                                                                          | Pakendi kõrgus                          | 70 mm                     |
| LED-indikaatorid                       | ✓                                                                             | Pakendi kaal                            | 1,35 kg                   |
| Seinale kinnitatav                     | ✓                                                                             | Logistika andmed                        |                           |
|                                        |                                                                               | Harmonized System (HS) kood             | 85176990                  |



6935364052904



6935364052911



0845973089764



845973089764

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date