

## TP-Link TL-FC311B-20 meediakonverter 1000 Mbit/s Üksikrežiim Must

Brand : TP-Link

Product code: TL-FC311B-20

Product name : TL-FC311B-20

TP-Link TL-FC311B-20. Andmete edastamise maksimaalne määr: 1000 Mbit/s, Võrgustandardid: IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet-liidese tüüp: Gigabit Ethernet. Maksimaalne ülekandekaugus: 2000 m, Kiustruktuur: Üksikrežiim, Toetatud kiudkaabli läbimõõt: 9/125 µm. LED-indikaatorid: Tegevus, Link, Võimsus, Toote värv: Must. Fiiberoptiline pistmik: SC, Ühenduvustehnoloogia: Juhtmega ühendatud. Väljundpinge: 5 V, Väljundvool: 0,6 A





NetworkPowerMaximum data transfer rate *1000 Mbit/sOutput voltage5 VMaximum data transfer rate *16EE 802.3, IEEE 802.3ab, IEEEOutput current0.6 ANetworking standardsGigabit EthernetWeight & dimensionsMetagene singer sin	
Networking standardsIEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3zOutput current0.6 ANetworking standardsSigabit Ethernet 6 Gigabit EthernetWidth94.5 mmEthernet LAN data rates10,100,1000 Mbit/sDepth73 mmData transfer rate1000 Mbit/sDepth73 mmPerformanceOperational conditions27 mmMaximum transfer distance *2000 mOperating temperature (T-T)0 - 50 °CWavelength-division multiplexing (WDM)·Storage temperature (T-T)-40 - 70 °CFiber mode structureSingle-modeStorage relative humidity (H-H)10 - 90%Fiber cable diameters supported (core/cladding)9/125 µmPackaging contentKo denetwinded	
Networking standards802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3zWeight & dimensionsEthernet interface typeGigabit EthernetWidth94.5 mmEthernet LAN data rates10,100,1000 Mbit/sDepth73 mmData transfer rate1000 Mbit/sDepth27 mmPerformanceMaximum transfer distance *2000 mOperational conditionsWavelength-division multiplexing (WDM)2000 m0 - 50 °CFiber mode structureSingle-modeStorage temperature (T-T)-40 - 70 °CFiber cable diameters supported (core/cladding)9/125 μmPackaging content5 - 90%	
IEEE 802.3zWeight & dimensionsEthernet interface typeGigabit EthernetWidth94.5 mmEthernet LAN data rates10,100,1000 Mbit/sDepth73 mmData transfer rate1000 Mbit/sHeight27 mmPerformanceMaximum transfer distance *2000 mOperational conditionsWavelength-division multiplexing (WDM)*Operating temperature (T-T)0 - 50 °CFiber mode structureSingle-modeStorage temperature (T-T)-40 - 70 °CFiber cable diameters supported (core/cladding)9/125 µmPackaging content5 - 90%	
Ethernet LAN data rates 10,100,1000 Mbit/s Depth 73 mm Data transfer rate 1000 Mbit/s Height 27 mm Performance 2000 m Operational conditions 0-50 °C Maximum transfer distance 2000 m Operating temperature (T-T) 0-50 °C Wavelength-division multiplexing (WDM) Fiber mode structure Single-mode Single-mode Storage relative humidity (H-H) 10-90% Fiber cable diameters supported 9/125 µm Packaging content	
Data transfer rate1000 Mbit/sHeight27 mmPerformanceOperational conditionsMaximum transfer distance *2000 mOperating temperature (T-T)0 - 50 °CWavelength-division multiplexing (WDM)·Storage temperature (T-T)-40 - 70 °CFiber mode structureSingle-modeStorage relative humidity (H-H)10 - 90%Fiber cable diameters supported (core/cladding)9/125 μmPackaging contentContent	
Performance Operational conditions   Maximum transfer distance * 2000 m Operating temperature (T-T) 0 - 50 °C   Wavelength-division multiplexing (WDM) ✓ Storage temperature (T-T) -40 - 70 °C   Fiber mode structure Single-mode Operating relative humidity (H-H) 10 - 90%   Fiber cable diameters supported (core/cladding) 9/125 μm Packaging content	
Maximum transfer distance *   2000 m   Operating temperature (T-T)   0 - 50 °C     Wavelength-division multiplexing (WDM)   -   Storage temperature (T-T)   -40 - 70 °C     Fiber mode structure   Single-mode   Operating relative humidity (H-H)   10 - 90%     Fiber cable diameters supported (core/cladding)   9/125 μm   Packaging content	
Wavelength-division multiplexing (WDM) Storage temperature (T-T) -40 - 70 °C   Piber mode structure Single-mode Operating relative humidity (H-H) 10 - 90%   Fiber cable diameters supported (core/cladding) 9/125 μm Packaging content 5 - 90%	
(core/cladding) Packaging content	
Features AC adapter included	
Internal * Quick installation guide	
LED indicators Activity, Link, Power Packaging data	
Product colour Black Package width 165 mm	
Ports & interfaces Package depth 204 mm	
Connectivity technology Wired Package height 65 mm	
Ethernet LAN (RJ-45) ports 1 Package weight 560 g	
Fiber ports quantity 1 Logistics data	
Fiber optic connector * SC Harmonized System (HS) code 85176990	
DC-in jack	





6935364010591

6935364072926

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.