



TP-Link Omada EAP620 HD traadita kohtvõrgu pääsupunkt 1201 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link

Product family: Omada

Product code: EAP620 HD

Product name : EAP620 HD

TP-Link Omada EAP620 HD. 2,4 GHz, 5 GHz, Andmete edastamise maksimaalne määr: 1201 Mbit/s. Turvaalgoritmid: SNMP, SNMPv2, SNMPv3, SSH, WEP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3, WPA3-PSK. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge



Funktsioonid		Juhtimisfunktsioonid	
2,4 GHz *	✓	Veebipõhine haldus	✓
5 GHz *	✓	Logiserver	✓
6 GHz *	✗	Ülendatav püsivara	✓
Andmete edastamise maksimaalne määr *	1201 Mbit/s	Pesad & liidesed	
Maksimaalne andmeedastuskiirus (2.4 GHz)	574 Mbit/s	Ethernet LAN (RJ-45) pordid *	1
Maksimaalne andmeedastuskiirus (5 GHz)	1201 Mbit/s	DC-pistik	✓
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s	Võimsus	
Sagedusriba	2.4 - 5 GHz	Power over Ethernet tugi *	✓
Võrgustandardid	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at	Toide üle võrgu (PoE) toetatud tüüp	Active PoE, Passive PoE
Kaabeldustehnoloogia	10/100/1000Base-T(X)	DC-pingevahemik	12 V
Kasutajate arv	1020 kasutaja(t)	Disain	
Automaatne kanalivalik	✓	Paigutus *	Lagi, Sein
Automaatne kanalite otsing	✓	Toote värv *	Valge
MIMO	✓	Lähtestusnupp	✓
MIMO tüüp	Multi User MIMO	LED-indikaatorid	✓
Hajaspektermeetod	OFDMA	Sertifikaat	CE, FCC, RoHS
Fit AP režiimi elemendid	Silmusvõrgud	Antenn	
VLAN-i tugi	✓	Antenni tüüp *	Sisemodem
Kiiruse piiramine	✓	Antenni suuna tüüp	Mitmesuunaline
Voo reguleerimise tugi	✓	Kaal ja mõõtmed	
Band Steering	✓	Laius	160 mm
Airtime Fairness (ATF)	✓	Sügavus	160 mm
Teenusekvaliteedi (QoS) tugi	✓	Kõrgus	33 mm
BeamForming	✓	Pakendi andmed	
Saatja võimsus (CE)	20/23 dbm	Pakendi tüüp	Karp
Saatja võimsus (FCC)	23 dbm	Pakendi sisu	
		Kaasnevate toodete arv	1 tk
		Paigalduskomplekt	✓
		Kiirstarti juhend	✓

Turvalisus		Töötingimused	
Turvaalgoritmid *	SNMP, SNMPv2, SNMPv3, SSH, WEP, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3, WPA3-PSK	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
MAC-aadresside filtreerimine	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Remote Authentication Dial-In User Service (RADIUS)	✓	Hoiustamistemperatuur (T-T)	-40 - 70 °C
Pääsuloend (ACL)	✓	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti



4897098687765



6935364030742



6935364030759

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.