



TP-Link CPE510 traadita kohtvõrgu pääsupunkt 300 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link

Product code: CPE510

Product name : CPE510

TP-Link CPE510. Andmete edastamise maksimaalne määr: 300 Mbit/s. Turvaalgoritmid: 64-bit WEP, 128-bit WEP, 152-bit WEP, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK. Ethernet LAN-i andmeedastuskiirused: 10,100 Mbit/s. Power over Ethernet tugi. Toote värv: Valge



Funktsioonid		Disain	
Andmete edastamise maksimaalne määr *	300 Mbit/s	Toote värv *	Valge
WiFi andmeedastuskiirus (maksimaalne)	300 Mbit/s	Lähtestusnupp	✓
Ethernet LAN-i andmeedastuskiirused	10,100 Mbit/s	LED-indikaatorid	✓
Sagedusriba	5.15 - 5.85 GHz	Sertifikaat	FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark RoHS
Ribalaius	5 GHz	Sisemine	✗
Võrgustandardid	IEEE 802.11a, IEEE 802.11n	Antenn	
Maksimaalne leviala väljas	15000 m	Antenni elemendid	Integreeritud antenn
Vastuvõtja tundlikkus	802.11a: 54M: -75dBm, 48M: -76dBm, 36M: -83dBm, 6-24M: -95dBm 802.11n: MCS15: -73dBm, MCS14: -74dBm, MCS13: -76dBm, MCS12: -80dBm, MCS11: -83dBm, MCS10: -88dBm, MCS9: -90dBm, MCS8: -93dBm, MCS7: -73dBm, MCS6: -74dBm, MCS5: -76dBm, MCS4: -80dBm, MCS3: -83dBm, MCS2: -88dBm, MCS1: -90dBm, MCS0: -93dBm	Antennide arv	1
		Antennivõimenduse tase (maksimaalne)	13 dBi
		Toimimine	
		Sisesehitatud protsessor	✓
		Välkmälu	8 MB
		Sisemälu	64 MB
		Ühilduvad operatsioonisüsteemid	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux.
Turvalisus		Kaal ja mõõtmed	
Turvaalgoritmid *	64-bit WEP, 128-bit WEP, 152-bit WEP, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK	Laius	224 mm
MAC-aadresside filtreerimine	✓	Sügavus	75 mm
		Kõrgus	60 mm
Protokollid		Pakendi sisu	
Haldusprotokollid	TDMA	Kaablid kaasa arvatud	Vahelduvvool
Juhtimisfunktsioonid		Töötingimused	
Veebipõhine haldus	✓	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Haldusplatvorm	Pharos Control	Kasutamistemperatuur (T-T)	-30 - 70 °C
		Hoiustamistemperatuur (T-T)	-40 - 70 °C
Pesad & liidesed		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 95 protsenti
Ethernet LAN (RJ-45) pordid *	1	Logistika andmed	
WAN-ühendus	Ethernet (RJ-45)	Harmonized System (HS) kood	85176990
Võimsus			
Power over Ethernet tugi *	✓		
AC-sisendpinge	100 - 240 V		
AC-sisendsagedus	50 - 60 Hz		
Sisendvool	0.8 A		

Võimsus

Võimsustarve (tüüpiline)

13 W



0804904109407




804904109407



6935364082260



0801940481498



801940481498

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.