



## TP-Link TL-SG116 võrgulüliti Mittejuhitav Gigabit Ethernet (10/100/1000) Must

Brand : TP-Link

Product code: TL-SG116

Product name : TL-SG116



TP-Link TL-SG116. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 16. Täisdupleks. MAC-aadresside tabel: 8000 sisestust, Lülitusvõime: 32 Gbit/s. Võrgustandardid: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Alalisvoolu sisendpinge: 9 V. Seinale kinnitatav



Juhtimisfunktsioonid		Andmeedastus	
Lüliti tüüp *	Mittejuhitav	Paketi puhvermälu	4,1 MB
Teenusekvaliteedi (QoS) tugi	✓	<b>Turvalisus</b>	
<b>Pesad &amp; liidesed</b>		IGMP-jälgimine	✓
RJ-45 Etherneti ühenduse pesade arv *	16	Tsükli kaitse	✓
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	<b>Disain</b>	
Gigabitise Etherneti (vask) portide arv	16	Püstikmontaaž *	✗
<b>Võrgustumine</b>		Toote värv	Must
Võrgustandardid *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Korpuse materjal	Metall
10G-tugi *	✗	LED-indikaatorid	✓
Etherneti vaskaablite tehnoloogia	10BASE-T, 100BASE-TX, 1000BASE-T	Seinale kinnitatav	✓
Toetatud kaablitüübid	Cat3, Cat4, Cat5, Cat5e, Cat6	<b>Võimsus</b>	
Pordipeegeldus	✓	Kaasas toiteplokk *	✓
Täisdupleks	✓	AC-sisendpinge	220 V
Voo reguleerimise tugi	✓	AC-sisendsagedus	50 Hz
Linkide koondamine	✓	Alalisvoolu sisendpinge	9 V
Levandamise torni kontroll	✓	Sisendvool	0.6 A
Kiiruse piiramine	✓	Elektritarbimine (max)	9,3 W
Auto MDI/MDI-X	✓	<b>Internet elektrivõrgu kaudu (PoE)</b>	
Automaatne ühildumine	✓	Power over Ethernet tugi *	✗
Kaablipikkuse tuvastus	✓	<b>Töötingimused</b>	
VLAN-i tugi	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Virtuaalse LANi elemendid	Protocol-based VLAN, Tagged VLAN	Hoiustamistemperatuur (T-T)	-40 - 70 °C
VLAN-ide arv	32	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
<b>Andmeedastus</b>		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Lülitusvõime *	32 Gbit/s	Soojuse hajumine	31,68 BTU/h
Edastamise kiirus	23,81 Mpps	<b>Kaal ja mõõtmed</b>	
MAC-aadresside tabel *	8000 sisestust	Laius	286 mm
Ladusta-ja-edasta	✓	Sügavus	111,7 mm

Andmeedastus		Kaal ja mõõtmed	
Ootejärjekordade arv	4	Kõrgus	25,4 mm
Hiigelkaadrite tugi	✓	Pakendi andmed	
Hiigelkaadrite	9000	Kaablid kaasa arvatud	Vahelduvvool
		Kiirstardi juhend	✓
		Logistika andmed	
		Harmonized System (HS) kood	85176990

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date