

GIGABYTE AORUS P1200W toiteallika komponent 1200 W 20+4 pin ATX ATX Must

Brand : GIGABYTE

Product code: GP-AP1200PM

Product name : AORUS P1200W

GIGABYTE AORUS P1200W. Koguvõimsus: 1200 W, AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 50 - 60 Hz. Emaplaadi toitepistik: 20+4 pin ATX, Emaplaadi toitekaabli pikkus: 61 cm, SATA toitekaabli pikkus: 150,650 mm. Otstarve: PC, Toiteploki (PSU) standard: ATX, 80 PLUS sertifikaat: 80 PLUS Platinum. Toote värv: Must, Jahutuse tüüp: Aktiivne, Ventilaatori läbimõõt: 14 cm. Kaablid kaasa arvatud: CPU, PCIe, Peripheral (Molex), SATA



| Võimsus | | Pesad & liidesed | |
|--|--|--------------------------------|-------------------------------------|
| Koguvõimsus * | 1200 W | Flopidraivi toitepistik | 2 |
| AC-sisendpinge * | 100 - 240 V | Flopidraivi pistmik | ✓ |
| AC-sisendsagedus | 50 - 60 Hz | Flopijami kaabli pikkus | 15 cm |
| Sisendvool | 15 - 7.5 A | Kaabelduse tüüp | Täielikult modulaarne |
| Võimsusteguri korrigeerimise (PFC) tüüp | Aktiivne | Toimimine | |
| Hoide aeg | 16 ms | 80 PLUS sertifikaat * | 80 PLUS Platinum |
| Tõhusus | 92 protsenti | Emaplaadi toetatud kujutegurid | ATX |
| Toite kaitsefunktsioonid | Ülevool, Ülevõimsus, Ülepinge, Lühis, Alapinge | Otstarve * | PC |
| | | Toiteploki (PSU) standard * | ATX |
| | | ATX-versioon | 2.31 |
| | | Laagertehnoloogia | DBB |
| | | Keskmine tõrkeintervall (MTBF) | 100000 h |
| Pesad & liidesed | | Disain | |
| Emaplaadi toitepistik * | 20+4 pin ATX | Toote värv | Must |
| Emaplaadi toitekaabli pikkus | 61 cm | Jahutuse tüüp | Aktiivne |
| SATA-toitepistmike arv | 16 | Ventilaatori läbimõõt | 14 cm |
| SATA toitekaabli pikkus | 150,650 mm | Ventilaatorite arv | 1 ventilaator(id) |
| Välisseadmete (Molex) toitepistikud (4 kontakti) * | 6 | Ventilaatori paiknemine | Ülaosa |
| Välise (Molex) toitekaabli pikkus | 120,150,600 mm | Valgustus | ✓ |
| EPS toitepistik (4+4 pinn) | ✓ | Pakendi sisu | |
| PCI Expressi toitepistikud (6 + 2 kontakti) | 10 | Kaablid kaasa arvatud | CPU, PCIe, Peripheral (Molex), SATA |
| PCI Express toitekaabli pikkus | 65 cm | Kaal ja mõõtmed | |
| CPU-toitepistik (4 + 4 kontakti) | ✓ | Laius | 150 mm |
| CPU toitekaabli pikkus | 65 cm | Sügavus | 86 mm |
| ATX-toitepistik (20 + 4 kontakti) | ✓ | Kõrgus | 160 mm |
| | | Logistika andmed | |
| | | Harmonized System (HS) kood | 84733020 |



4719331552251

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date