



LG 55XS4J infoekraan Digital signage lameekraan 139,7 cm (55") IPS WiFi 4000 cd/m² Full HD Must WebOS 24/7



Brand : LG

Product code: 55XS4J

Product name : 55XS4J

LG 55XS4J. Tootedisain: Digital signage lameekraan. Ekraani diagonaal: 139,7 cm (55"), Ekraani tehnoloogia: IPS, Ekraani resolutsioon: 1920 x 1080 pikslit, Ekraani heledus: 4000 cd/m², HD tüüp: Full HD. WiFi. Töötunnid (tunnid/päevad): 24/7. Installitud operatsioonisüsteem: WebOS. Toote värv: Must



Ekraan		Disain	
LED tagantvalguse tüüp	Direct-LED	VESA paigaldamine *	✓
Ekraani diagonaal *	139,7 cm (55")	VESA-paigaldusliidesed	600 x 400 mm
Ekraani tehnoloogia *	IPS	Raami laius (alumine)	1,2 cm
Ekraani resolutsioon *	1920 x 1080 pikslit	Raami laius (külg)	9,9 mm
Ekraani heledus *	4000 cd/m ²	Raami laius (ülemine)	1,2 cm
HD tüüp *	Full HD		
Puuetundlik ekraan *	✗	Toimimine	
Loomulik kuvasuhe	16:9	Otstarve *	Universaalne
Reaktsiooniaeg	9 ms	Ümbritseva valguse andur	✓
Kontrastsustase (tüüpiline)	1000:1	Töötunnid (tunnid/päevad)	24/7
Kontrasti suhe (dünaamiline)	500000:1		
Vaatenurk, horisontaalne	178°	Võimsus	
Vaatenurk, vertikaalne	178°	Võimsustarve (tüüpiline) *	375 W
Ekraani värvide arv	16,7 miljonit värvi	AC-sisendpinge	100 - 240 V
Ähmasuse määr	3 protsenti	AC-sisendsagedus	50-60 Hz
RGB-värviruum	NTSC	Soojuse hajumine	1280 BTU/h
		Arvutisüsteem	
Pesad & liidesed		Arvutisüsteem *	✓
HDMI-portide arv *	2	Sisemälu	16 GB
HDMI-versioon	1.4	Installitud operatsioonisüsteem	WebOS
DVI-port *	✗		
DisplayPort arv *	1	Kaal ja mõõtmed	
USB port *	✓	Laius	1235,5 mm
USB-portide hulk	1	Sügavus	85,4 mm
USB versioon	2.0	Kõrgus	709,4 mm
Ethernet LAN *	✓	Kaal	26 kg
Ethernet LAN (RJ-45) pordid	1		
WiFi *	✓	Pakendi andmed	
Audio (v, p) väljund	1	Pakendi kaal	31,2 kg
RS-232C	✓		
Kaugsisend (IR)	1	Pakendi sisu	
		Kaugjuhtimispuul on nõutud	✓
Audio		Akad kaasa arvatud	✓
Sisseehitatud kõlar(id) *	✓	Kaablid kaasa arvatud	Vahelduvvool, HDMI, IR
Sisseehitatud kõlarite arv	2		
RMS-nimivõimsus	20 W	Töötingimused	
		Kasutamistemperatuur (T-T)	0 - 40 °C
Disain		Suhteline õhuniiskus kasutamisel (H-H)	10 - 80 protsenti
Tootedisain *	Digital signage lameekraan	Sertifikaadid	
Toetatud paigutus *	Hoonesisene	Sertifikaat	CB / NRTL EMC FCC Class "A" / CE / KC / VCCI ErP
Lehekülje paigutus	Horisontaalne/vertikaalne		

Disain

Toote värv *

Must

Funktsioonid

Soojuse hajutamine (max)

1365 BTU/h



8806091355010

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date