

Chieftec PowerUp GPX-850FC toiteallika komponent 850 W 20+4 pin ATX ATX Must

Brand : Chieftec

Product family: PowerUp

Product code: GPX-850FC

Product name : GPX-850FC

Chieftec PowerUp GPX-850FC. Koguvõimsus: 850 W, AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 47 - 63 Hz. Emaplaadi toitepistik: 20+4 pin ATX, Emaplaadi toitekaabli pikkus: 65 cm, SATA toitekaabli pikkus: 500,650,800 mm. Otstarve: PC, Toiteploki (PSU) standard: ATX, 80 PLUS sertifikaat: 80 PLUS Gold. Toote värv: Must, Ventilaatori läbimõõt: 12 cm, Ventilaatorite arv: 1 ventilaator(id). Kaablid kaasa arvatud: Vahelduvvool, CPU, PCIe, Peripheral (Molex), SATA



Võimsus		Pesad & liidesed	
Koguvõimsus *	850 W	PCI Expressi toitepistikud (6 + 2 kontakti)	6
AC-sisendpinge *	100 - 240 V	PCI Express toitekaabli pikkus	65 cm
AC-sisendsagedus	47 - 63 Hz	CPU-toitepistik (4 + 4 kontakti)	✓
Sisendvool	12 A	CPU toitekaabli pikkus	80 cm
Võimsusteguri korrigeerimise (PFC) tüüp	Aktiivne	ATX-toitepistik (20 + 4 kontakti)	✓
Kombineeritud võimsus (+3,3 V)	110 W	Flopidraivi toitepistik	1
Kombineeritud võimsus (+12 V)	846 W	Kaabelduse tüüp	Täielikult modulaarne
Kombineeritud võimsus (+5 V)	110 W	Toimimine	
Kombineeritud võimsus (-12 V)	3,6 W	80 PLUS sertifikaat *	80 PLUS Gold
Kombineeritud võimsus (+5 Vsb)	12,5 W	Otstarve *	PC
Maksimaalne väljundvool (+3,3 V)	20 A	Toiteploki (PSU) standard *	ATX
Maksimaalne väljundvool (+12 V)	70,5 A	ATX-versioon	2.53
Maksimaalne väljundvool (+5 V)	20 A	Sertifikaat	80PLUS Gold
Maksimaalne väljundvool (-12 V)	0,3 A	Disain	
Maksimaalne väljundvool (+5 Vsb)	2,5 A	Toote värv	Must
Toite kaitsefunktsioonid	Ülevool, Ülevõimsus, Ülepinge, Lühis, Alapinge	Ventilaatori läbimõõt	12 cm
Pesad & liidesed		Ventilaatorite arv	1 ventilaator(id)
Emaplaadi toitepistik *	20+4 pin ATX	Ventilaatori paiknemine	Ülaosa
Emaplaadi toitekaabli pikkus	65 cm	Sisse/välja lüliti	✓
SATA-toitepistikute arv	9	Pakendi sisu	
SATA toitekaabli pikkus	500,650,800 mm	Kaablid kaasa arvatud	Vahelduvvool, CPU, PCIe, Peripheral (Molex), SATA
Välisseadmete (Molex) toitepistikud (4 kontakti) *	3	Kaal ja mõõtmed	
Välise (Molex) toitekaabli pikkus	500,650,800,950 mm	Laius	150 mm
		Sügavus	140 mm
		Kõrgus	86 mm
		Kaal	2,4 kg
		Pakendi andmed	
		Pakendi kaal	2,95 kg
		Pakendi tüüp	Karp

Logistika andmed

Harmonized System (HS) kood 84733020



0753263077202



753263077202

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.