



Dahua Technology XVR5104HS-4KL-I3 Must

Brand : Dahua Technology

Product code: DH-XVR5104HS-4KL-I3

Product name : XVR5104HS-4KL-I3



Dahua Technology XVR5104HS-4KL-I3. Toote värv: Must, Maksimaalne video resolutsioon: 3840 x 2160 pikslit, Videopakkimise formaadid: H.264, H.264+, H.265, H.265+. Video sisendkanalid: 4 kanalid, Audioväljund: 1 RCA. Ethernet-liidese tüüp: Kiire Ethernet, Toetatud võrguprotokollid: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. Kõvaketta liides: SATA, Maksimaalne kõvakettamaht: 16 TB. Toite tüüp: DC (alalisvool), Alalisvoolu ping: 12 V, Võimsustarve (tüüpiline): 7 W

Toimimine		Võrgustumine	
Maksimaalne video resolutsioon	3840 x 2160 pikslit	Ethernet LAN	✓
Videopakkimise formaadid	H.264, H.264+, H.265, H.265+	Ethernet-liidese tüüp	Kiire Ethernet
Toetatud audioformaadid	G.711 A-law, G.711 µ-law, PCM	Ethernet LAN (RJ-45) pordid	1
Varundamise funktsioon	✓	Toetatud võrguprotokollid	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Video salvestamise kiirus	30 fps		
Videohõive kiirus (PAL)	25 fps		
Videohõive kiirus (NTSC)	30 fps		
Video kaotuse tuvastamine	✓		
Video liikumisandur	✓		
Kanalite arv	4 kanalid		
Toote värv *	Must		
Installitud operatsioonisüsteem	Kaasas LINUX		
PTZ-kontroll	✓		
Püstiku mahutavus	1U		
Sertifikaat	FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024		
Pesad & liidesed		Kõvaketas	
Video sisendkanalid	4 kanalid	Toetatud kõvaketaste arv	1
BNC-sisendpordid	4	Kõvaketta liides	SATA
HDMI-portide arv	1	Maksimaalne kõvakettamaht	16 TB
Audiosisend	1		
Audioväljund	1 RCA		
USB 2.0 portide arv	2		
RS-485 pordid	1		
		Võimsus	
		Toite tüüp	DC (alalisvool)
		Alalisvoolu ping	12 V
		Võimsustarve (tüüpiline)	7 W
		Kaal ja mõõtmed	
		Laius	260 mm
		Sügavus	237,9 mm
		Kõrgus	47,6 mm
		Kaal	530 g
		Pakendi andmed	
		Pakendi laius	333 mm
		Pakendi sügavus	315 mm
		Pakendi kõrgus	89 mm
		Pakendi kaal	1,07 kg
		Ekraan	
		Sisseehitatud ekraan	✗
		Töötingimused	
		Kasutamistemperatuur (T-T)	-10 - 55 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-AUG-2024. Prints or copies of Information are only valid on the printed Publication date