

Dahua Technology Lite HAC-HDW1500TMQ(-A) Ülepea IP süsteemiga turvakaamera Hoonesisene & hooneväline 2880 x 1620 pikslit Lagi/sein

Product name : HAC-HDW1500TMQ(-A)

Dahua Technology Lite HAC-HDW1500TMQ(-A). Tüüp: IP süsteemiga turvakaamera, Toetatud paigutus: Hoonesisene & hooneväline, Ühenduvustehnoloogia: Juhtmega ühendatud. Kinnituse tüüp: Lagi/sein, Toote värv: Valge, Toote kuju: Ülepea. Minimaalne valgustus: 0,005 lx, Rotatsiooni nurk: 360°, Kaldenurk: 0 - 78°. Anduri tüüp: CMOS, Optilise sensori suurus: 25,4 / 2,7 mm (1 / 2.7"). Märkamiskaugus: 63,6 m, Jälgimiskaugus: 25,4 m, Äratundmiskaugus: 12,7 m





IP security camera	Night vision Night vision *	
IP security camera	Night vision *	
	NIGHT VISIOH "	✓
Indoor & outdoor	LED type	IR
yy * Wired	Video	
CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)	Maximum resolution * Total megapixels * Supported graphics resolutions Noise reduction Noise reduction technology Gain control type Privacy masking Back Light Compensation (BLC) Digital Wide Dynamic Range	2880 x 1620 pixels 5 MP 2880 x 1620 2D noise reduction Auto/Manual
	(DWDR)	✓
Dome	Smart IR	✓
Ceiling/wall	Audio	
White	Signal-to-Noise Ratio (SNR)	65 dB
Metal, Plastic IP67	Security	
	Mirror	✓
✓	Power	
✓ 0.005 lx	Power source type * DC output voltage	DC 12
360°	Operational conditions	
0 - 78° 0 - 360°	Operating temperature (T-T) Storage temperature (T-T)	-40 - 60 °C -40 - 60 °C
Auto, Manual		
	Ceiling/wall White Metal, Plastic IP67 O.005 Ix 360° 0 - 78°	Ceiling/wall White Signal-to-Noise Ratio (SNR) Metal, Plastic IP67 Security Mirror Power Power source type * 0.005 lx 360° Operational conditions 0 - 78° Operating temperature (T-T)

Image sensor		Weight & dimensions	
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Width	99.1 mm
Sensor type *	CMOS	Depth	99.1 mm
Lens system		Height	121.9 mm
Detect distance	63.6 m	Weight	400 g
Observe distance	25.4 m	Packaging data	
Recognize distance	12.7 m	Package weight	600 g
Focal length range	2.88 mm	Packaging content	
Maximum aperture number	1.6	Number of cameras *	1
Identify distance	6.4 m	Number of Cameras	1



6939554951589

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.