



## TP-Link Archer AX23 juhtmevaba ruuter Gigabit Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Must

**Brand :** TP-Link

**Product family:** Archer

**Product code:** ARCHER AX23

**Product name :** Archer AX23

TP-Link Archer AX23. WAN-ühenduse tüüp: RJ-45. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN edastuskiirus (max): 1800 Mbit/s. Ethernet LAN-liidese tüüp: Gigabit Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s, Võrgustandardid: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Turvaalgoritmid: 64-bit WEP, 128-bit WEP, WMM, WPA, WPA-PSK, WPA2, WPA2-PSK, NAT-funktsionaalsus: Port Forwarding, Port Triggering, UPnP, DMZ. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Must



WAN-ühendus		Turvalisus	
Ethernet WAN *	✓	NAT-funktsionaalsus	Port Forwarding, Port Triggering, UPnP, DMZ
SIM kaardi ava *	✗		
WAN-ühenduse tüüp	RJ-45		
Juhtmevaba LAN-i omadused		Protokollid	
Wi-Fi laineala *	Kaks sagedusala (2,4 GHz / 5 GHz)	DHCP-klient	✓
Wi-Fi standard *	Wi-Fi 6 (802.11ax)	DHCP-server	✓
WLAN edastuskiirus (max) *	1800 Mbit/s	Universaalne Plug and Play (UPnP)	✓
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)		
WLAN edastuskiirus (esimene laineala)	574 Mbit/s		
WLAN edastuskiirus (teine laineala)	1201 Mbit/s		
Võrgustumine		Disain	
Ethernet LAN *	✓	Toote värv	Must
Ethernet LAN-liidese tüüp *	Gigabit Ethernet	Toote tüüp *	Laua peale asetatav ruuter
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s		
Võrgustandardid	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n		
Täisdupleks	✓		
Voo reguleerimise tugi	✓		
Portide suunamine	✓		
Dünaamiline DNS (DDNS)	✓		
Staatiline ruutimine	✓		
Mobiilivõrk		Pakendi sisu	
4G	✓	Kaablid kaasa arvatud	LAN (RJ-45)
		AC-adapter kaasa arvatud	✓
		Garantiikaart	✓
		Kiirpaigaldusjuhend	✓
Pesad & liidised		Antenn	
Ethernet LAN (RJ-45) pordid *	4	Antenni kujundus *	Väline
USB port *	✓	Antennipistmiku tüüp	SMA
USB 2.0 portide arv	1		
		Funktsioonid	
		Sisesehitatud protsessor	✓
		Protsessori sagedus	1500 MHz
		Protsessorituumad	2
		Sertifikaat	FCC, CE, RoHS
		Võimsus	
		Toiteallika tüüp *	DC (alalisvool)
		Väljundpinge	12 V
		Väljundvool	1 A
		Töötingimused	
		Kasutamistemperatuur (T-T)	0 - 40 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti

Pesad & liidesed		Süsteeminõuded	
DC-pistik	✓		
Juhtimisfunktsioonid			
Veebipõhine haldus	✓		
Internetipõhine kasutusjuhend	✓		
Ribalaiuse juhtimine	✓		
Lähtestusnupp	✓		
WPS-nupp	✓		
Turvalisus			
Turvaalgoritmid	64-bit WEP, 128-bit WEP, WMM, WPA, WPA-PSK, WPA2, WPA2-PSK		
Külalise juurdepääs	✓		
Pääsuloend (ACL)	✓		
IP-aadresside filtreerimine	✓		
URL-i filtreerimine	✓		
Süsteemisündmuste logi	✓		
DMZ-tugi	✓	Toetatud Windowsi operatsioonisüsteemid	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Võrguaadresside transleerimine (NAT)	✓	Toetatud Linuxi operatsioonisüsteemid	✓
		Toetatud Maci operatsioonisüsteemid	✓
		Kaal ja mõõtmed	
		Laius	260,2 mm
		Sügavus	135 mm
		Kõrgus	41,6 mm
		Pakendi andmed	
		Pakendi laius	500 mm
		Pakendi sügavus	350 mm
		Pakendi kõrgus	395 mm
		Pakendi kaal	730 g
		Logistika andmed	
		Harmonized System (HS) kood	85176990



4897098687048



4897098683927

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date