

Samsung OM46B Digital signage lameekraan 116,8 cm (46") LCD WiFi 4000 cd/m² Full HD Must Tizen 5.0 24/7

Brand : Samsung

Product family: OMB

Product code:
LH46OMBEBGBXEN

Product name : OM46B



Samsung OM46B. Tootedisain: Digital signage lameekraan. Ekraani diagonaal: 116,8 cm (46"), Ekraani tehnoloogia: LCD, Ekraani resolutsioon: 1920 x 1080 pikslit, Ekraani heledus: 4000 cd/m², HD tüüp: Full HD. WiFi. Töötunnid (tunnid/päevad): 24/7. Installitud operatsioonisüsteem: Tizen 5.0. Toote värv: Must

Ekraan		Disain	
Paneeli tüüp	VA	VESA-paigaldusliidesed	400 x 400 mm
Ekraani diagonaal *	116,8 cm (46")	Raami laius (alumine)	1,99 cm
Ekraani tehnoloogia *	LCD	Raami laius (külg)	1,99 cm
Ekraani resolutsioon *	1920 x 1080 pikslit	Raami laius (ülemine)	1,99 cm
Ekraani heledus *	4000 cd/m ²	Toimimine	
HD tüüp *	Full HD	Integreeritud TV-tuuner	✗
Puuetundlik ekraan *	✗	Töötunnid (tunnid/päevad)	24/7
Loomulik kuvasuhe	16:9	HDCP	✓
Reaktsiooniaeg	6 ms	Rahvusvahelise kaitse (IP) kood	IP5X
Kontrastsustase (tüüpiline)	6000:1	HDCP versioon	2.2
Dünaamilise kontrastimäära turunduslik nimi	Mega kontrast	Võimsus	
Vaatenurk, horisontaalne	178°	Võimsustarve (tüüpiline) *	350 W
Vaatenurk, vertikaalne	178°	Võimsustarve (unerežiim)	0,5 W
Pikslitihedus	0,53 x 0,53 mm	AC-sisendpinge	100 - 240 V
Värvide küllastus	72 protsenti	AC-sisendsagedus	50 - 60 Hz
Horisontaalskaneerimise ulatus	15 - 135 kHz	Arvutisüsteem	
Vertikaalne skaneerimisulatus	24 - 75 Hz	Sisemine mälu maht	8 GB
RGB-värviruum	NTSC	Installitud operatsioonisüsteem	Tizen 5.0
Pesad & liidesed		Kaal ja mõõtmed	
HDMI-portide arv *	2	Ekraani laius	1062 mm
HDMI-versioon	2.0	Ekraani sügavus	54,5 mm
HDMI sisendportide arv	2	Ekraani kõrgus	616,6 mm
DVI-port *	✗	Ekraani kaal	18,2 kg
DisplayPort arv *	1	Pakendi andmed	
DisplayPort sisend	1	Pakendi laius	1189 mm
USB port *	✓	Pakendi sügavus	158 mm
USB-portide hulk	1	Pakendi kõrgus	757 mm
Ethernet LAN *	✓	Pakendi kaal	23 kg
Ethernet LAN (RJ-45) pordid	2	Töötingimused	
WiFi *	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Komposiitvideo väljund	1	Suhteline õhuniiskus kasutamisel (H-H)	10 - 80 protsenti
RS-232 liides	✓	Tehnilised andmed	
RS-232C	✓	Audio sisend (Mini jack pistik)	✗
Infrapuna port	✓	Muud funktsioonid	
Disain		Audioväljund	Stereo Mini Jack
Tootedisain *	Digital signage lameekraan		
Toote värv *	Must		
VESA paigaldamine *	✓		

Muud funktsioonid

Bluetooth



Videoväljund

Yes



8806094039474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date