



Dahua Technology XVR5116HS-I3 DVR-salvesti Must

Brand : Dahua Technology

Product code: XVR5116HS-I3

Product name : XVR5116HS-I3



Dahua Technology XVR5116HS-I3. Toote värv: Must, Maksimaalne video resolutsioon: 3840 x 2160 pikslit, Videopakkimise formaadid: H.264, H.264+, H.265, H.265+. Audiosisend: 1 RCA, Audioväljund: 1 RCA, Videosisend: HDCVI/AHD/TVI/CVBS/IP. Ethernet-liidese tüüp: Kiire Ethernet, Toetatud võrguprotokollid: HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P. Kõvaketta liides: SATA, Maksimaalne kõvakettamaht: 16 TB. Toite tüüp: DC (alalisvool), Alalisvoolu ping: 12 V

Toimimine		Pesad & liidesed	
Maksimaalne video resolutsioon	3840 x 2160 pikslit	USB 2.0 portide arv	1
Videopakkimise formaadid	H.264, H.264+, H.265, H.265+	USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk	1
Toetatud audioformaadid	G.711 A-law, G.711 μ -law, PCM	Videosisend	HDCVI/AHD/TVI/CVBS/IP
Varundamise funktsioon	✓	RS-485 pordid	1
Videohõive kiirus (PAL)	25 fps	Võrgustumine	
Videohõive kiirus (NTSC)	30 fps	Ethernet LAN	✓
Video kaotuse tuvastamine	✓	Ethernet-liidese tüüp	Kiire Ethernet
Video liikumisandur	✓	Ethernet LAN (RJ-45) pordid	1
Kanalite arv	16 kanalid	Toetatud võrguprotokollid	HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P
Toote värv *	Must	Kõvaketas	
Analoogsignaali vormingu süsteem	NTSC, PAL	Kõvaketta liides	SATA
Installitud operatsioonisüsteem	Kaasas LINUX	Maksimaalne kõvakettamaht	16 TB
Video voogesitus	✓	Võimsus	
Dual stream tugi	✓	Toite tüüp	DC (alalisvool)
Bitsagedus	32 Kbit/s	Alalisvoolu ping	12 V
PTZ-kontroll	✓	Kaal ja mõõtmed	
Püstiku mahutavus	1U	Laius	260 mm
Sertifikaat	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 FCC: Part 15 Subpart B	Sügavus	237,4 mm
Pesad & liidesed		Kõrgus	47,6 mm
BNC-sisendpordid	16	Kaal	1,17 kg
HDMI-portide arv	1	Pakendi andmed	
VGA (D-Sub) väljundpordid	1	Pakendi laius	89 mm
Audiosisend	1 RCA	Pakendi sügavus	333 mm
Audioväljund	1 RCA	Pakendi kõrgus	315 mm
		Töötingimused	
		Kasutamistemperatuur (T-T)	-10 - 55 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-AUG-2024. Prints or copies of Information are only valid on the printed Publication date