

TP-Link JetStream TL-SG2210P võrgulüliti Juhitav L2/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product family: JetStream

Product code: TL-SG2210P


Product name : TL-SG2210P

TP-Link JetStream TL-SG2210P. Lüliti tüüp: Juhitav, Lüliti kiht: L2/L4. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 8. MAC-aadresside tabel: 8000 sisestust, Lülitusvõime: 20 Gbit/s. Võrgustandardid: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Toitepistmik: Alaldi sisendi pesa. Power over Ethernet tugi



Management features		Security	
Switch type *	Managed	BPDU filtering/protection	1
Switch layer	L2/L4	IP-MAC-Port binding	 Image: A set of the set of the
Quality of Service (QoS) support Web-based management	<i>i</i>	Authentication	MAC-based authentication, Port- based authentication
ARP inspection	 Image: A second s	Multicast features	
Ports & interfaces		Multicast support	1
Basic switching RJ-45 Ethernet ports quantity *	8	Multicast Listener Discovery (MLD) snooping	 Image: A start of the start of
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Protocols	
type * SFP module slots quantity	2	IPv4 & IPv6 features	Dual stack IPv4/IPv6
Power connector	– DC-in jack	Design	
Network		Product colour	Black
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	LED indicators	1
		Performance	
		Firmware upgradeable	1
		Power	
10G support *	x	Power supply included *	1
Cable types supported	Cat3, Cat4, Cat5, Cat5e	AC input voltage	100 - 240 V
Port mirroring	 Image: A set of the set of the	AC input frequency	50 - 60 Hz
Flow control support	1	Power consumption (max)	77.8 W
Link aggregation	✓	Power over Ethernet (PoE)	
Broadcast storm control	1	Power over Ethernet (PoE) *	1
Rate limiting	1	Operational conditions	
Auto MDI/MDI-X	1	Operating temperature (T-T)	0 - 40 °C
Spanning tree protocol	1	Storage temperature (T-T)	-40 - 70 °C

Network		Operational conditions	
Auto-negotiation	✓	Operating relative humidity (H-H)	10 - 90%
VLAN support	 Image: A set of the set of the	Storage relative humidity (H-H)	5 - 90%
Data transmission		Weight & dimensions	
Switching capacity * 2	20 Gbit/s	Width	209 mm
Forwarding rate	14.9 Mpps	Depth	126 mm
MAC address table *	8000 entries	Height	26 mm
Jumbo frames support	1	Packaging content	
Jumbo frames	9000	Quick start guide	✓
Security		Certificates	
Access Control List (ACL)	✓	Certification	CE, FCC, RoHS
IGMP snooping	 Image: A set of the set of the	Logistics data	
Static port security	1	Harmonized System (HS) code	85176990
SSH/SSL support	1	·	





845973088668

0845973088668

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.