


## GIGABYTE GP-UD750GM toiteallika komponent 750 W 20+4 pin ATX ATX Must

**Brand :** GIGABYTE

**Product code:** GP-UD750GM

**Product name :** GP-UD750GM

GIGABYTE GP-UD750GM. Koguvõimsus: 750 W, AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 50 - 60 Hz. Emaplaadi toitepistikmik: 20+4 pin ATX, Emaplaadi toitekaabli pikkus: 61 cm, SATA toitekaabli pikkus: 150,300,450,600 mm. Otstarve: PC, Toiteploki (PSU) standard: ATX, 80 PLUS sertifikaat: 80 PLUS Gold. Tootes värv: Must, Jahutuse tüüp: Aktiivne, Ventilatori läbimõõt: 12 cm. Kaablid kaasa arvatud: CPU, PCIe, Peripheral (Molex), SATA



<b>Power</b>		<b>Ports &amp; interfaces</b>	
Total power *	750 W	PCI Express power cable length	60 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	CPU power cable length	60 cm
Input current	12 A	ATX power connector (20+4 pin)	✓
Power Factor Correction (PFC) type	Active	Floppy drive power connector	1
Combined power (+3.3V)	105 W	Floppy disk drive connector	✓
Combined power (+12V)	732 W	Floppy disk drive cable length	15 cm
Combined power (+5V)	105 W	Cabling type	Fully-Modular
Combined power (-12V)	3.6 W	<b>Performance</b>	
Combined power (+5Vsb)	15 W	80 PLUS certification *	80 PLUS Gold
Max output current (+3.3V)	20 A	Purpose *	PC
Max output current (+12V)	61 A	Power supply unit (PSU) form factor *	ATX
Max output current (+5V)	20 A	ATX version	2.31
Max output current (-12V)	2.3 A	Bearing technology	HYB
Max output current (+5Vsb)	3 A	Mean time between failures (MTBF)	100000 h
Hold time	16 ms	<b>Design</b>	
Efficiency	90%	Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage
<b>Ports &amp; interfaces</b>		Product colour	Black
Motherboard power connector *	20+4 pin ATX	Cooling type	Active
Motherboard power cable length	61 cm	Fan diameter	12 cm
Number of SATA power connectors	8	Number of fans	1 fan(s)
SATA power cable length	150,300,450,600 mm	Fan location	Top
Peripheral (Molex) power connectors (4-pin) *	3	On/off switch	✓
Peripheral (Molex) power cable length	120,500 mm	<b>Packaging content</b>	
		Cables included	CPU, PCIe, Peripheral (Molex), SATA
		<b>Weight &amp; dimensions</b>	
		Width	150 mm

Ports & interfaces		Weight & dimensions	
EPS power connector (4+4 pin)	✓	Depth	140 mm
PCI Express power connectors (6+2 pin)	4	Height	86 mm
Logistics data			
Harmonized System (HS) code		84733020	



4719331552671

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.