



## Dahua Technology VTO3312Q-P video-sisesidesüsteem 2 MP Hall

**Brand :** Dahua Technology

**Product code:** DHI-VTO3312Q-P

**Product name :** VTO3312Q-P

Dahua Technology VTO3312Q-P. Toetatud videoformaadid: H.264, H.265. Megapiksel: 2 MP, Toetatud videorežiimid: 720p, 1080p, Anduri tüüp: CMOS. LED-i tüüp: IR. Häälakoodekid: G.711a, G.711u, PCM. Toote värv: Hall, Rahvusvahelise kaitse (IP) kood: IP65, IK-kood: IK08



Technical details		Design	
Connectivity technology *	Wired	IK code	IK08
Colour *	✗	Housing material	Aluminium
Speakerphone *	✓	Control type	Buttons
Maximum number of cameras supported *	1	Placement supported	Vertical
Door station control	✓	Proper use	Outdoor
VoIP protocols	RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF	<b>Storage</b>	
Wall mountable	✓	Memory card slot	✓
Built-in microphone	✓	Compatible memory cards	MicroSD (TransFlash), SD
Automatic gain control	✓	Maximum memory card size	256 GB
Motion detection function	✓	<b>Network</b>	
RFID reader	✓	Ethernet interface type	Fast Ethernet
Sustainability compliance	✓	Ethernet LAN data rates	10,100 Mbit/s
Compliance certificates	CE, Federal Communications Commission (FCC)	Ethernet LAN (RJ-45) ports	1
<b>Display</b>		Cabling technology	10/100Base-T(X)
Touchscreen	✗	Power over Ethernet (PoE)	✓
Video formats supported	H.264, H.265	Supported network protocols	RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF
<b>Camera</b>		<b>Power</b>	
Megapixel (approx.)	2 MP	Outdoor unit power type	DC
Supported video modes	720p, 1080p	AC adapter output voltage	48 V
Sensor type	CMOS	AC adapter output current	1 A
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Power consumption (typical)	8 W
Maximum frame rate	30 fps	Power consumption (standby)	4 W
Viewing angle, horizontal	125°	<b>Operational conditions</b>	
Viewing angle, vertical	65°	Operating temperature (T-T)	-40 - 60 °C
		Operating relative humidity (H-H)	10 - 90%

<b>Night vision</b>		<b>Weight &amp; dimensions</b>	
Night vision	✓	Width	107.2 mm
LED type	IR	Depth	30 mm
<b>Audio</b>		Height	188.1 mm
Built-in speaker(s)	✓	Weight	570 g
Noise-canceling	✓	<b>Packaging data</b>	
Voice codecs	G.711a, G.711u, PCM	Outdoor unit included *	✓
<b>Design</b>		Package weight	780 g
Product colour *	Grey	<b>Logistics data</b>	
International Protection (IP) code	IP65	Quantity per pack	1 pc(s)
		Minimum order quantity	1 pc(s)



6923172532565

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.