



Dahua Technology XVR5104HS-I3 Must

Brand : Dahua Technology

Product code: DH-XVR5104HS-I3

Product name : XVR5104HS-I3



Dahua Technology XVR5104HS-I3. Toote värv: Must, Maksimaalne video resolutsioon: 1920 x 1080 pikslit, Videopakkimise formaadid: H.264, H.264+, H.265, H.265+. Video sisendkanalid: 4 kanalid, Audiosisend: 1 RCA, Audioväljund: 1 RCA. Ethernet-liidese tüüp: Kiire Ethernet, Toetatud võrguprotokollid: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. Kõvaketta liides: SATA, Maksimaalne kõvakettamaht: 16 TB. Toite tüüp: DC (alalisvool), Alalisvoolu ping: 12 V, Võimsustarve (tüüpiline): 4 W

Toimimine		Pesad & liidesed	
Maksimaalne video resolutsioon	1920 x 1080 pikslit	Audiosisend	1 RCA
Videopakkimise formaadid	H.264, H.264+, H.265, H.265+	Audioväljund	1 RCA
Toetatud audioformaadid	G.711 A-law, G.711 μ -law, PCM	USB 2.0 portide arv	2
Varundamise funktsioon	✓	RS-485 pordid	1
Video salvestamise kiirus	30 fps	Võrgustumine	
Video kaotuse tuvastamine	✓	Ethernet LAN	✓
Video liikumisandur	✓	Ethernet-liidese tüüp	Kiire Ethernet
Taasesituse toetatud resolutsioonid	1920 x 1080, 1280 x 1024, 1280 x 720	Ethernet LAN (RJ-45) pordid	1
Kanalite arv	4 kanalid	Toetatud võrguprotokollid	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Toote värv *	Must	Kõvaketas	
Analoogsignaali vormingu süsteem	NTSC, PAL	Toetatud kõvaketaste arv	1
Installitud operatsioonisüsteem	Kaasas LINUX	Kõvaketta liides	SATA
Helisüsteem	kahe-suunaline	Maksimaalne kõvakettamaht	16 TB
Maksimaalne kaadrisagedus	60 fps	Võimsus	
Video voogesitus	✓	Toite tüüp	DC (alalisvool)
Dual stream tugi	✓	Alalisvoolu ping	12 V
PTZ-kontroll	✓	Võimsustarve (tüüpiline)	4 W
Püstiku mahutavus	1U	Kaal ja mõõtmed	
Sertifikaat	FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024	Laius	260 mm
Pesad & liidesed		Sügavus	237,9 mm
Video sisendkanalid	4 kanalid	Kõrgus	47,6 mm
BNC-sisendpordid	4	Kaal	1 kg
BNC-väljundpordid	1	Pakendi andmed	
HDMI-portide arv	1	Pakendi laius	333 mm
VGA (D-Sub) väljundpordid	1	Pakendi sügavus	315 mm
		Pakendi kõrgus	89 mm
		Pakendi kaal	1,4 kg
		Töötingimused	
		Kasutamistemperatuur (T-T)	-10 - 55 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-AUG-2024. Prints or copies of Information are only valid on the printed Publication date