



Dahua Technology Lite NVR2108HS-8P-S3 võrguvideosalvesti (NVR) 1U Must



Brand : Dahua Technology

Product family: Lite

Product code: NVR2108HS-8P-S3

Product name :
NVR2108HS-8P-S3

Dahua Technology Lite NVR2108HS-8P-S3. Video sisendkanalid: 8 kanalid, Videosalvestusrežiimid: 720p, 1080p, Installitud operatsioonisüsteem: Kaasas LINUX. Maksimaalne salvestusmaht: 16 TB, Kõvaketta liides: SATA. Ethernet LAN-i andmeedastuskiirused: 10,100 Mbit/s, Toetatud võrguprotokollid: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; DDNS; Alarm Server;.... Püstiku mahutavus: 1U, LED-indikaatorid: HDD, Võrk, Võimsus, Toote värv: Must. Väljundvool: 2 A, Väljundpinge: 48/53 V

Toimimine		Pesad & liidesed	
Video sisendkanalid *	8 kanalid		HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); P2P
Videosalvestusrežiimid	720p, 1080p	Toetatud võrguprotokollid	
Video liikumisandur	✓		
Installitud operatsioonisüsteem	Kaasas LINUX		
Varundamise funktsioon	✓		
Videokoodekid	Smart H.265; H.265; Smart H.264; H.264	Funktsioonid	
Helikoodekid	PCM; G711A; G711U; G726	Püstikmontaaž	✓
Taasesitusrežiimid	Paus, Play, Stoptuli	Püstiku mahutavus	1U
Maksimaalne kaadrisagedus	30 fps	LED-indikaatorid	HDD, Võrk, Võimsus
Sisendi ribalaius	80 Mbit/s	Toote värv	Must
Väljundi ribalaius	60 Mbit/s	Sertifikaat	CE: EN62368-1; EN55032; EN55024; EN55035; EN61000-3-2; EN61000-3-3; EN50130-4 FCC: Part 15 Subpart B
Salvestusrežiimid	Manuaal		
Kõvaketas		Protsessor	
Installitud kõvaketaste arv *	1	Sisesehitatud protsessor	✓
Maksimaalne salvestusmaht *	16 TB	Võimsus	
Kõvaketta liides *	SATA	Väljundvool	2 A
Pesad & liidesed		Väljundpinge	48/53 V
Ethernet LAN (RJ-45) pordid *	1	Süsteeminõuded	
Power over Ethernet tugi	✓	Toetatud mobiilsed operatsioonisüsteemid	Android, iOS
Ethernet LAN-i andmeedastuskiirused	10,100 Mbit/s	Brauseritugi	Chrome; IE 9 or later; Firefox
Toide üle võrgu (PoE) pesade arv	8	Töötingimused	
HDMI-väljund	✓	Kasutamistemperatuur (T-T)	-10 - 55 °C
HDMI-portide arv	1	Suhteline õhuniiskus kasutamisel (H-H)	10 - 93 protsenti
VGA (D-Sub) väljundpordid	1	Kaal ja mõõtmed	
USB 2.0 portide arv	2	Laius	260 mm
Audio RCA sisendid	1	Sügavus	232,7 mm
Audio RCA väljundid	1	Kõrgus	47,6 mm
		Kaal	890 g
		Pakendi laius	117 mm
		Pakendi sügavus	373 mm
		Pakendi kõrgus	307 mm
		Pakendi kaal	1,94 kg



6923172533241

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-AUG-2024. Prints or copies of Information are only valid on the printed Publication date