Printing

KYOCERA ECOSYS M2040dn Laser A4 1200 x 1200 DPI 40 lk/min

Brand : KYOCERA

Product family: ECOSYS

Product code: 1102S33NL0

Product name : M2040dn

KYOCERA ECOSYS M2040dn. Printimistehnoloogia: Laser, Printimine: Mono printimine, Maksimaalne resolutsioon: 1200 x 1200 DPI. Kopeerimine: Mono kopeerimine, Maksimaalne kopeerimisresolutsioon: 600 x 600 DPI. Skaneerimine: Värviskaneerimine, Optilise skaneerimise resolutsioon: 600 x 600 DPI. Dupleksfunktsioonid: Koopia, Print, Skaneerimine. Maksimaalne ISO A-seeria paberi suurus: A4. Otseprintimine. Toote värv: Must, Valge





i i i i i i i i i i i i i i i i i i i		i ores a meeriaces	
Duplex printing mode	Auto	Standard interfaces	Ethernet, USB 2.0
Print technology *	Laser	Direct printing *	1
Printing *	Mono printing	USB port	1
Duplex printing *	1	USB 2.0 ports quantity	2
Maximum resolution *	1200 x 1200 DPI	Network	
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Wi-Fi *	×
Duplex print speed (black, normal guality, A4/US Letter)	20 ppm	Ethernet LAN *	1
Warm-up time	17 s	Cabling technology	10/100/1000Base-T(X)
Time to first page (black, normal)	6.4 s	Ethernet LAN data rates	10,100,1000 Mbit/s
N-in-1 print function		Bluetooth	×
Tray priority settings function		Near Field Communication (NFC)	×
N-up printing	2, 4		Apple AirPrint, Google Cloud Print,
Barcode printing	2,4	Mobile printing technologies	Kyocera Mobile Print, Mopria Print Service
1 5	-		
Watermark printing		Performance	
Secure printing	J	Maximum internal memory	1536 MB
Booklet printing function	1	Card reader integrated	1
Poster printing function	1	Internal memory *	512 MB
Borderless printing	×	Compatible memory cards	SD, SDHC
Copying		Built-in processor	1
		Processor family	ARM Cortex-A9
Duplex copying *	1	Processor frequency	800 MHz
Duplex copying mode	Auto		

Ports & interfaces

Publication date: 02-JAN-2025. Prints or copies of Information are only valid on the printed Publication date

Commission of the second se			
Copying		Performance	
Copying *	Mono copying	Sound pressure level (printing)	52 dB
Maximum copy resolution *	600 x 600 DPI	Sound pressure level (copying)	52 dB
Time to first copy (black, normal) Maximum number of copies	6.4 s	Sound pressure level (quiet mode)	48 dB 29 dB
Copier resize	999 copies 25 - 400%	Sound power level (standby)	29 UD
N-in-1 copy function	∠s +00/0 ✓	Design	
N-in-1 copy function (N=)	2, 4	Product colour *	Black, White
Copy programming function	_, . ✓	Market positioning *	Business
ID-card copy function	1	Built-in display *	
Scanning		Display Display number of lines	LCD 5 lines
-			5 11165
Duplex scanning *		Power	
Duplex scanning mode Scanning *	Auto Colour scanning	Power consumption (average operating)	661 W
Optical scanning resolution *	600 x 600 DPI	Power consumption (printing)	661 W
Scan technology	CIS	Power consumption (copying)	661 W
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Power consumption (ready)	21 W
Scan speed (colour)	23 ppm	Power consumption (sleep)	1 W
Scan speed (black)	40 ppm	Energy Star Typical Electricity Consumption (TEC)	1.66 kWh/week
Image formats supported	JPG, TIF, TIFF	AC input voltage	220 - 240 V
Document formats supported	PDF, XPS	AC input frequency	50 - 60 Hz
Scan drivers _	TWAIN, WIA	System requirements	
Fax		Windows operating systems	
Faxing *	×	supported	✓
Features			Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Recommended duty cycle	1000 - 2500 pages per month		Sierra, Mac OS X 10.13 High Sierra,
Maximum duty cycle *	50000 pages per month	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5
Duplex functions *	Copy, Print, Scan	Mac operating systems supported	Leopard, Mac OS X 10.6 Snow
Digital sender			Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X
Number of print cartridges *	1 Plack		10.9 Mavericks
Printing colours *	Black Microsoft XPS, PCL 5e, PCL 6, PCL	Linux operating systems supported	1
Page description languages	XL, PostScript 3, TIFF	Operational conditions	
Number of printer fonts	93	Operating relative humidity (H-H)	10 - 80%
Replacement cartridges	TK-1170 (7.200 pagina's)	Storage temperature (T-T)	-20 - 40 °C
Input & output capacity		Operating temperature (T-T)	10 - 32.5 °C
Total number of input trays *	1	Storage relative humidity (H-H)	10 - 90%
Total input capacity *	250 sheets	Operating altitude	0 - 3500 m
Total output capacity *	150 sheets	Non-operating altitude	0.6 - 15000 m
Paper tray 1 input capacity	250 sheets	Certificates	
Multi-Purpose tray Multi-Purpose tray input capacity	100 sheets	Waste Electrical and Electronic Equipment (WEEE) compliance	1
Paper input type	Cassette, Paper tray	Certification	GS, TÜV, CE, ISO 9001, ISO 14001
Auto document feeder (ADF)	 ✓ 	Sustainability	
Auto document feeder (ADF) input	50 sheets	-	Blue Angel, EPEAT Silver, ENERGY
capacity		Sustainability certificates	STAR
Maximum number of input trays	3	Weight & dimensions	
Maximum input capacity Maximum output capacity	850 sheets 150 sheets	Width	417 mm
	150 Sheets	Depth	412 mm
Paper handling		Height	437 mm
Maximum ISO A-series paper size *	A4 216 x 356 mm	Weight	19 kg
Maximum print size Paper tray media types *	Plain paper	Packaging data	
ISO A-series sizes (A0A9) *	A4, A5, A6	Package width	541 mm
ISO B-series sizes (B0B9)	B5, B6	Package depth	555 mm
Non-ISO print media sizes	Legal, Letter	Package height	572 mm
Custom media width	70 - 216 mm	Package weight	25 kg
Custom media length	148 - 356 mm		


Paper handling

Paper tray media weight			
Multi-Purpose Tray media weight			
Duplex media weight			

60 - 163 g/m² 60 - 220 g/m² 60 - 163 g/m²

Packaging content

Cartridge(s) included	1			
Included cartridge capacity (black)	3600 pages			
Imaging unit included	1			
Cables included	AC			
Logistics data				
Harmonized System (HS) code	84433100			
Technical details				
Compliance certificates	REACH, RoHS			
Other features				
Cartridge type	TK-1170			





632983040294

0632983040294

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.