Dahua Technology Lite HAC-HDW1200TLMQ-0280B Ülepea CCTV turvakaamera Hoonesisene & hooneväline Lagi/sein/post

Brand : Dahua Technology

Product family: Lite

Product code: DH-HAC-HDW1200TLMQ-0280B

Product name : HAC-HDW1200TLMQ-0280B

Dahua Technology Lite HAC-HDW1200TLMQ-0280B. Tüüp: CCTV turvakaamera, Toetatud paigutus: Hoonesisene & hooneväline, Ühenduvustehnoloogia: Juhtmega ühendatud. Kinnituse tüüp: Lagi/sein/post, Toote värv: Valge, Toote kuju: Ülepea. Rotatsiooni nurk: 360°, Objektiivi vaatenurk, horisontaalne: 85°, Objektiivi vaatenurk, vertikaalne: 45°. Anduri tüüp: CMOS. Fikseeritud fookuskaugus: 2,8 mm, Märkamiskaugus (lai): 38,6 m, Jälgimiskaugus (lai): 15,4 m

Type *CCTV security cameraLED typeIR Number of Illumination LEDsIR Network of Illumination LED	Performance		Night vision	
Paceament supportedInder So outdoorNumber of illumination LEDs1Connectivy technologyMedicaMedicaMedicaWide Dynamic Range(WDR)ATotal magapixels on a policy280 x720 (Hp 720), 960 x440, 900 x700, 960 x440, 900 x700, 960 x700,	Type *	CCTV security camera		IR
Wide Wide Wide Day/injkit modeDay/injkit mode Day/injkit modeTotal megapixels *2MPDay/injkit mode Number of languages11Supported graphics resolution Soported graphics resolution200 x 576, 1920 x 1080 (HD 1080)Languages supportEnglish, French, German, Spanish, Portuguese, Italian, Ispanese, Korean, Russian, Polish Moise reductionSupported video modes1080b, 720, 960pCertificationCE (ENS5032:2015, EN G1000-3:2013, EN S1020:X1010-A1:2014) FC (ENS5023:2015, EN G1000-3:2013, EN S1020:X1010-A1:2014) CE (ENS5023:2017, CP at 15 subpart8, ANP CR4 X-7 EC ANT IS Subpart8, ANP	Placement supported *			1
Daylight mode< India megapies2 kmpNumber of languages11Supported graphics resolutions200 x 720 (HD 720), 960 x 480, 960 x 576, 1220 x 1080 (HD 1080)Languages supportEnglish, French, German, Spanish, Korean, Russian, PolishSupported video modes30 fpsKorean, Russian, PolishNoise reductionCE (FNS5032-2015, ENNoise reduction technology2D noise reductionCE (FNS5032-2014, EN S1000- 151000-52071Sine orduction technology2D noise reductionDisto 30-22014, EN S1000- 151000-22014, EN S1000- 151000-2000-10000- 151000- 151000-22014, EN S1000- 151000-22014, E	Connectivity technology *	Wired	Video	
Daymight mode'Supported graphics resolutions1280 x 720 (HD 720), 960 x 480, 960 x 576, 1920 x 1080 (HD 1080)Number of languages11Supported yide modes1080p, 720p, 960 x 480, 960 x 576, 1920 x 1080 (HD 1080)Languages supportEnglish, French, German, Spanish, Korean, Russian, Polish Korean, Russian, Polish Biton, 3-2:2014, EN 1000, 3-3:2013, EN 5003/2:2014, HA1:2014, FCC (CFR 47 FCC Part 15 subpart8, ANS G63.4:2014) UL (UL60950-1) (UL60950-1) (UL60950-2:2014, EN 1000, 3-3:2013, EN 5003/2:2014, PCC (CFR 47 FCC Part 15 subpart8, ANS G63.4:2014) UL (UL60950-1) (UL60950-1) (UL6091-1) (UL6095-1) (UL60950-1) (UL6091-1) (UL6095-1) (UL6091-1) (UL6095-1) (UL6091-1) (UL6091-	Wide Dynamic Range (WDR)	 Image: A set of the set of the	Total megapixels *	2 MP
Number of languages11It was proved video modes900 83 76, 1220 x 1000 (HD 1000)Languages supportEnglish, French, German, Spanish, Korean, Russian, Polish Korean, Russian, Polish (CE (FWS5032-2015, EN Gino 0-22014, EN 61000- 3-3:2013, ENS5024:2014-A1:2015 Sine reduction technology30 pisCertificationCE (FWS5032-2015, EN Gino 0-23:2014, EN 61000- 3-3:2013, ENS5024:2014-A1:2014) (UI (UI 0050-14-CAUC)SA C22: (CER 47 FCC Part 15 subparts), ANS (CE (FR 47 FCC Part 15 subparts), ANS (UI (UI 0050-14) CAUC) (UI (UI 0050-14) CAUC) (Direction Fatures) (Portaction (FRC))And (FIFDesignDome (CE (IIII) (Wall/PoleAndite-Ford fator (Poduct colout)Celling/Wall/PoleAndite-Protection features (Direction (FP) code)Dome (Signal-to-Noise Ratio (SNR))65 dBCamera CameraVinite islantSignal-to-Noise Ratio (SNR)65 dBCamera apa control (Signal data code)Vinite islandSignal-to-Noise Ratio (SNR))65 dBCamera apa control (Signal data code)Signal-to-Noise Ratio (SNR)Signal-to-Noise Ratio (SNR)Celling (Signal data code)Camera apit control (Signal data code)Signal-to-Noise Ratio (SNR)Signal-to-Noise Ratio (SNR)Signal-to-Noise Ratio (SNR)Camera apit control <br< td=""><td>Day/night mode</td><td>✓</td><td>U .</td><td></td></br<>	Day/night mode	✓	U .	
Languages supportPrime uses, halian, Japanese, Korean, Nussian, Polish Sidou0-3-22014, EN 61000- 3-32013, ENS024-2010+A1:2014) ENS033-2017, ENS024-2010+A1:2014) ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2011+A1:2014)ENS04 ENS034-2014-2014 ENS034-2014-2014 ENS034-2014-2014 ENS034-2014-2014 ENS034-2014-2014 ENS034-2014-2014 ENS034-2014-2014 ENS034-2014-2014-2014 ENS034-2014-2014-2014-2014-2014-2014-2014-201	Number of languages	11	Supported graphics resolutions	
CertificationKorean, Russian, Polish CE (ENS5032:2015, EN 61000-3:2:2014, EN 61000- 3:3:2013, ENS5024:2010+A1:2015 EN 550133:2017, ENS50130:4:2011+A1:2014 PCC (CFR 47 FCC PAT 15 subparts, ANS CG3.4:2011+A1:2014) FCC (CFR 47 FCC PAT 15 subparts, ANS CG3.4:2011+A1:2014) FCC (ULIG0950:1)-CAN(/CSA C22.2) Noise reduction technology Privacy masking Back Light Compensation (HLC) (ULIG0950:1)-CAN(/CSA C22.2) Noise reduction technology Privacy masking Back Light Compensation (HLC) (ULIG0950:1)-CAN(/CSA C22.2) Noise reduction technology Privacy masking Back Light Compensation (HLC) (ULIG0950:1)-CAN(/CSA C22.2) Noise reduction technology Privacy masking Privacy Pr	Languages support		11	
Certification Certification space (E (ENS5032:2015, EN S000-2) Noise reduction technology 2D noise reduction Saiz 0013, ENS5024:2014-A1:2014 PICC Gain control type Auto/Manual ENS 0330-4:2011+A1:2014 PICC Filp & mirror - FIND SIG0-4:2011+A1:2014 PICC Filp & mirror - CGR4 2014 UL (ULG0050-11-CANCSA C22.2 Mighlight Compensation (BLC) - Posign - - - Posign Celling/Wal/Pole Back Light Compensation (BLC) - Product colour * Dome Smart IR * Product colour * Metal Signal-Noise Ratio (SNR) 5 GB Product colour * Metal Signal-Noise Ratio (SNR) 5 GB Product colour * Metal Signal-Noise Ratio (SNR) 5 GB Product colour * Metal Signal-Noise Ratio (SNR) 5 GB Product colour * Metal Signal-Noise Ratio (SNR) 5 GB Camera Signal-Noise Ratio (SNR) Signal-Noise Ratio (SNR) Signal-Noise Ratio (SNR) Camera op control Proc Signal-Noise Ratio (SNR)	Languages support	5		•
Said 2013, ENS5024:2010 +A1:2014 Gain control type Auto/Manual Said control type Auto/Manual ENS035:2017, ENS5014:2010 +A1:2014 File & mirror Certification File & mirror Certification CGR 47 FCC Part 15 subparts, ANS (CGR 47 FCC Part 15 subparts, ANS (DUE 0000 FCR 4000 FCR 4		CE (EN55032:2015, EN		
EN \$503:2017, Filp & miror * CER 47 FCC Part 15 subparts, ANS Rek Light Compensation (BLC) * No.60950-11, CAN/CSA C22.2, No.60950-11, CAN/CSA C22.2, Back Light Compensation (BLC) * Posign Dome Smart IR * * Mounting type * Celling/Wal/Pole Smart IR * * Product colour * White Audio \$ * * Product colour * White Signal-to-Noise Ratio (SNR) \$ \$ \$ * Product colour * White Signal-to-Noise Ratio (SNR) \$ \$ \$ * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * </td <td></td> <td>61000-3-2:2014, EN 61000-</td> <td></td> <td></td>		61000-3-2:2014, EN 61000-		
DefinitionProject (CFA 47) CCP art 15 Subparite, AVCP (CFA 47) LUL (ULGOS) C1+CA/NCSA C22.2 No.60950-1)Privacy maskingI and the subparite and the subparit and				
C63.4-2014) UL (UL60950.1-CAN/CSA C22.2 No.60950.1)Back Light Compensation (BLC)PosignDomePice Pice Pice Pice Pice Pice Pice Pice	Certification			
No.60950-11 Highlight Compensation (HLC) ✓ Design Dome Digital Wide Dynamic Range ✓ Form factor * Dome Smart IR ✓ Mounting type * Ceiling/Wall/Pole Smart IR ✓ Product colour * White Audio ✓ Housing material Metal Signal-to-Noise Ratio (SNR) 65 dB Protection features Dust resistant Ketwork × Camera Vir.Fi* × × Camera pan control ✓ Ketwork × Minimum illumination Ok Storage × Angle of rotation 360° Bulctonth* X Angle of rotation 360° Storage × Tit angle range 0.78° Power × Pan range 0.360° Power consumption (typical) 2.9 W Pan range 0.360° Power consumption (typical) 2.9 W Camera shutter type Electronic Dover consumption (typical) 2.9 W Proges		•		
Design Digital Wide Dynamic Range (DWDR)				
Form factor * Dome (DWDR) * Mounting type * Ceiling/Wall/Pole Smart IR * Product colour * White Audio * Housing material Metal Signal-to-Noise Ratio (SNR) 65 dB Protection features Dust resistant Network * Camera * * * Camera pan control * * * Minimu illumination 0 k Storage * Angle of rotation 360° Storage * Protex viewing angle, horizontal 85° BNC output ports 1 Pan range 0 - 78° Power * Pan range 0 - 360° Power consumption (typical) 2.9 W Muite balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic Operating temperature (T-T) 40 - 60 °C Storage temperature (T-T) 40 - 60 °C Storage temperature (T-T) 40 - 60 °C Muite balance * Storage temperature (T-T)<		N0.00950-1)		v
Form factor* Dome Mounting type * Dome Celling/Wall/Pole Smart IR * Mounting type * Celling/Wall/Pole Audio - Product colour * Metal Signal-to-Noise Ratio (SNR) 5d B Protection features Dust resistant Retwork - Camera Import LAN * X- - Camera pan control * Signal-to-Noise Ratio (SNR) X- Angle of rotation Import LAN * X- - Minimu illumination Ix X- - Angle of rotation So So X- Lens viewing angle, horizontal So So X- Lens viewing angle, diagonal 100° Pores fauteraces - Pan range 0-360° Power consumption (typical) 2.9 W Camera shutter type Electronic Power consumption (typical) 2.9 W Camera shutter type Camera Power consumption (typical) 2.9 W Camera shutter type Camera Power consumption (typical) 2.9 W	Design			1
Product color *WhiteAudioHousing materialMetalSignal-to-Noise Ratio (SNR)65 dBProtection featuresDust resistantNetworkCameraIP67Ethernet LAN *×Camera·Bluetooth *Noise Ratio (SNR)Alonge Color *Camera pan control·Ethernet LAN *×Camera tilt control·Bluetooth *×Angle of rotation360°Built-in HDD *×Angle of rotation360°Ports & interfaces×Lens viewing angle, horizontal85°Ports & interfaces×Pan range0 - 360°Power2020Pan range0 - 360°Power consumption (typical)2.9 WCamera shutter typeElectronicPower consumption (typical)2.9 WProgressive scan·Qerating temperature (T-T)-40 - 60 °CSensor type *CMOSOperating relative humidity (H-H)0.9 5%Number of lenses *1Storage temperature (T-T)-40 - 60 °CNumber of lenses *1Storage temperature (T-T)-40 - 60 °C	Form factor *			1
Number of lenses Number of lenses<		-	Audio	
Protection features Dust resistant Network International Protection (IP) code IP67 Ethermet LAN * × Camera * Wi-Fi * × Camera pan control * Storage × Camera tilt control * Storage × Minimum illumination 0 kx Buetooth * × Angle of rotation 360° Built-in HDD * × Lens viewing angle, horizontal 85° Ports & interfaces × Lens viewing angle, diagonal 100° Power × Pan range 0 - 78° Power × Pan range 0 - 360° Power consumption (typical) 2.9 W Camera shutter type Lens rower consumption (typical) 2.9 W 2.9 W Camera shutter type Iectronic Operating temperature (T-T) -40 - 60 °C Progressive scan * Operating relative humidity (H-H) 0 - 95% Storage temperature (T-T) -40 - 60 °C Operating relative humidity (H-H) 0 - 95% Storage temperature (
Network Network Ethernet LAN * X Camera Vi-Fi * X Camera pan control Image and control X Camera pan control Image and control X Camera jul control Image and control X Minimum illumination 0 lx Storage X Angle of rotation 360° Bult-in HDD * X Angle of rotation 360° Bult-in HDD * X Lens viewing angle, horizontal S° BNC output ports Image ange Lens viewing angle, vertical 45° BNC output ports Image ange Pan range 0 - 78° Power consumption (typical) 2.9 W Pan range 0 - 360° Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage Image ange Progressive scan MOS More (t-T) 40 - 60 °C Storage temperature (T-T) 40 - 60 °C Storage temperature (T-T) 40 - 60 °C Storage tendive humidity (H-H) 0 - 95%				05 06
Camera Ethernet LAN * × Camera pan control ✓ Wi-Fi * × Camera pan control ✓ Bluetooth * × Camera tilt control ✓ Bluetooth * × Minimu illumination 0 lx Storage × Angle of rotation 0 lx Built-in HDD * × Angle of rotation 85° Built-in HDD * × Lens viewing angle, horizontal 85° Ports & interfaces × Lens viewing angle, vertical 45° BNC output ports 1 Pan range 0 - 78° Power × Pan range 0 - 360° Power consumption (typical) 2.9 W Camera shutter type Electronic Do output voltage 12 Progressive scan ✓ Operating temperature (T-T) -40 - 60 °C Sensor type * CMOS Operating relative humidity (H-H) 0 - 95% Number of lenses * 1 9 9	International Protection (IP) code		Network	
Camera pan controlMi-Fi*XCamera pan controlJanaBluetooth *XCamera tilt controlIStorageXMinimum illumination0 lxBuilt-in HDD *XAngle of rotation85°Built-in HDD *XLens viewing angle, horizontal85°BNC output ports1Lens viewing angle, vertical45°BNC output ports1100°0.78°PowerIIPan range0.360°Power consumption (typical)2.9 WPan range0.360°Power consumption (typical)2.9 WCamera shutter typeElectronicDC output voltage12Progressive scanIOperating temperature (T-T)40 - 60 °CSensor type *CMOSStorage temperature (T-T)40 - 60 °CLens system1Storage temperature (T-T)40 - 60 °CNumber of lenses *1Storage relative humidity (H-H)0.95%				×
Butecotrin* K Camera tilt control I Minimum illumination 0 lx Angle of rotation 360° Lens viewing angle, horizontal 85° Lens viewing angle, vertical 45° No° BNC output ports Lens viewing angle, diagonal 100° 111t angle range 0 - 78° Pan range 0 - 360° Vhite balance ATW Camera shutter type Electronic Progressive scan I Sensor type * CMOS Sensor type * CMOS Number of lenses * 1		<i>,</i>	Wi-Fi *	×
Minimum illumination O Ix Storage Angle of rotation 360° Built-in HDD * X Lens viewing angle, horizontal 85° Ports & interfaces I Lens viewing angle, vertical 45° BNC output ports 1 Lens viewing angle, vertical 0° Power I Lens viewing angle, diagonal 0° Power I Tilt angle range 0° 360° Power DC Pan range 0° 360° Power consumption (typical) 2.9 W Khite balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage 12 Progressive scan I Operating temperature (T-T) -40 - 60 °C Sensor type * CMOS Operating relative humidity (H-H) 0.95% Number of lenses * 1 9 95%			Bluetooth *	×
Angle of rotationB0°Built-in HDD*XLens viewing angle, horizontal85°Ports & interfacesLens viewing angle, vertical45°BNC output ports1Lens viewing angle, diagonal10°Power1Lint angle range0 - 36°Power source type *DPan range0.360°Power consumption (typical)2.9 WWhite balanceATWPower consumption (typical)2.9 WCamera shutter typeIetornicDcoutput voltage12Progressive scan*Operating temperature (T-T)40 - 60 °CSensor type *CMOSOperating relative humidity (H-H)0.95%Number of lenses *111			Storage	
Lens viewing angle, vertical 45° BNC output ports 1 Lens viewing angle, diagonal 100° BNC output ports 1 Tilt angle range 0 - 78° Power DC Pan range 0 - 360° Power source type * DC White balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage 12 Image sensor ✓ Operating temperature (T-T) -40 - 60 °C Progressive scan ✓ Storage temperature (T-T) -40 - 60 °C Sensor type * CMOS Operating relative humidity (H-H) 0 - 95% Number of lenses * 1 0 -40 - 60 °C	Angle of rotation		Built-in HDD *	×
Lens viewing angle, diagonal 100° Power If it angle range 0 - 78° Power Pan range 0 - 360° Power source type * DC White balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage 12 Image sensor ✓ Operating temperature (T-T) -40 - 60 °C Progressive scan ✓ Operating relative humidity (H-H) 0 - 95% Sensor type * 1 1	Lens viewing angle, horizontal		Ports & interfaces	
Tilt angle range 0 - 78° Power Pan range 0 - 360° Power source type * DC White balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage 12 Image sensor ✓ Operating temperature (T-T) -40 - 60 °C Progressive scan ✓ Operating relative humidity (H-H) 0 - 95% Sensor type * CMOS Operating relative humidity (H-H) 0 - 95% Number of lenses * 1 1 1	5 5 5		BNC output ports	1
Pan range 0 - 360° Power source type * DC White balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage 12 mage sensor Image sensor Operating temperature (T-T) -40 - 60 °C Sensor type * CMOS Storage temperature (T-T) -40 - 60 °C Lens system I Operating relative humidity (H-H) 0 - 95% Number of lenses * 1 Image sensor Image sensor			Power	
White balance ATW Power consumption (typical) 2.9 W Camera shutter type Electronic DC output voltage 12 Image sensor Operational conditions 0 Progressive scan <			Power source type *	DC
Camera shutter type Electronic DC output voltage 12 Image sensor Operational conditions Progressive scan 	White balance			
Progressive scan CMOS CMOS Coperating temperature (T-T) -40 - 60 °C -40 - 60 °C Operating relative humidity (H-H) 0 - 95% Storage relative humidity (H-H) 0 - 95% Number of lenses * 1	Camera shutter type		DC output voltage	12
Sensor type * CMOS Storage temperature (T-T) -40 - 60 °C Operating relative humidity (H-H) 0 - 95% Number of lenses * 1	Image sensor		Operational conditions	
Lens system Operating relative humidity (H-H) 0 - 95% Number of lenses * 1	Progressive scan	 Image: A second s	Operating temperature (T-T)	-40 - 60 °C
Lens system Storage relative humidity (H-H) 0 - 95% Number of lenses * 1	Sensor type *	CMOS		
Number of lenses * 1	Lens system		1 5 5 5 7 7	
	Number of lenses *	1	Storage relative numidity (H-H)	0 - 95%
Maximum aperture number 1.9	Maximum aperture number	1.9		

Lens system		Weight & dimensions	
Fixed focal length	2.8 mm	Height	88.1 mm
Detect distance (wide)	38.6 m	Diameter	11 cm
Observe distance (wide)	15.4 m	Weight	330 g
Recognize distance (wide)	7.7 m	Packaging data	
Identify distance (wide)	3.9 m	Package weight	440 g
Closest focusing distance	0.5 m		440 g
Night vision		Packaging content	
•		Number of cameras *	1
Night vision *	✓		
Night vision distance	30 m		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.