

QNAP QHora-301W juhtmevaba ruuter 10 Gigabit Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Valge

Brand : QNAP

Product code: QHORA-301W

Product name : QHora-301W



QNAP QHora-301W. WAN-ühenduse tüüp: RJ-45. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN edastuskiirus (max): 2475 Mbit/s. Ethernet LAN-liidese tüüp: 10 Gigabit Ethernet, Ethernet LAN-i andmeedastuskiirused: 1000,10000 Mbit/s, VPN-i jõudlus: 300 Mbit/s. Tulemüür: TCP, UDP, ICMP, TCP+UDP. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Valge



WAN-ühendus		Disain	
Ethernet WAN *	✓	Sisse/välja lüüti	✓
DSL WAN *	✗	Toote tüüp *	Laua peale asetatav ruuter
SIM kaardi ava *	✗	Pakendi sisu	
3G/4G USB modemi ühilduvus *	✗	Kaablid kaasa arvatud	Vahelduvvool, LAN (RJ-45)
WAN-ühenduse tüüp	RJ-45	Kiirpaigaldusjuhend	✓
Juhtmevaba LAN-i omadused		Antenn	
Wi-Fi laineala *	Kaks sagedusala (2,4 GHz / 5 GHz)	Antenni kujundus *	Sisemodem
Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Antennivõimenduse tase (maksimaalne)	5,2 dBi
WLAN edastuskiirus (max) *	2475 Mbit/s	Antennide arv	8
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Funktsioonid	
Võrgustumine		Sisesehitatud protsessor	✓
Ethernet LAN *	✓	Protsessori tootja	Qualcomm
Ethernet LAN-liidese tüüp *	10 Gigabit Ethernet	Protsessori mudel	Qualcomm IPQ8072A
Ethernet LAN-i andmeedastuskiirused	1000,10000 Mbit/s	Protsessori sagedus	2200 MHz
VPN-i jõudlus	300 Mbit/s	Protsessorituumad	4
Mobiilivõrk		Sisemälu	1000 MB
3G	✗	Välkmälu	4000 MB
4G	✗	Üheaegsete seansside arv (max)	50000
5G	✗	Sertifikaat	FCC, CE RED, RCM, NCC, BSMI, VCCI, IC, JATE, CCC, SRRC
Pesad & liidesed		Võimsus	
Ethernet LAN (RJ-45) pordid *	6	Toiteallika tüüp *	DC (alalisvool)
USB port *	✓	Väljundpinge	12 V
USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk	2	Võimsustarve (tüüpiline)	24 W
DC-pistik	✓	Väline toiteadapter	✓
Juhtimisfunktsioonid		Töötingimused	
Lähtestusnupp	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
WPS-nupp	✓	Suhteline õhuniiskus kasutamisel (H-H)	5 - 95 protsenti
Turvalisus		Kaal ja mõõtmed	
Tulemüür	✓	Laius	250 mm
Tulemüür	TCP, UDP, ICMP, TCP+UDP	Sügavus	180 mm
Vanemlik kontroll	✓	Kõrgus	48 mm
		Kaal	1,9 kg

Protokollid		Pakendi andmed	
Universaalne Plug and Play (UPnP)	✓	Pakendi kaal	2,2 kg
Disain		Logistika andmed	
Toote värv	Valge	Harmonized System (HS) kood	85176990
Seinale kinnitav	✓		



4713213517840

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date