

TP-Link Omada EAP653 traadita kohtvõrgu pääsupunkt 2976 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link Product family: Omada Product code: EAP653


Product name: EAP653

TP-Link Omada EAP653. 2,4 GHz, 5 GHz, Andmete edastamise maksimaalne määr: 2976 Mbit/s. Turvaalgoritmid: HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA, WPA2, WPA3. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge

Features		Management features	
2.4 GHz *	✓	Web-based management	✓
5 GHz *	✓	Syslog	✓
6 GHz *	×	Firmware upgradeable	✓
Maximum data transfer rate *	2976 Mbit/s	Ports & interfaces	
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Ethernet LAN (RJ-45) ports *	1
Maximum data transfer rate (5 GHz)	2402 Mbit/s	DC-in jack	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Power	
Frequency band	2.4 - 5 GHz	Power over Ethernet (PoE) *	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE	DC voltage range	12 V
	802.11h	Design	
Cabling technology Number of users	10/100/1000Base-T(X) 250 user(s)	Placement *	Ceiling, Wall
	250 user(s)	Product colour *	White
Automatic channel selection		Reset button	✓
Automatic channel scanning	✓	LED indicators	✓
MIMO		Antenna	
MIMO type	Multi User MIMO		Internal
Spread spectrum method	OFDMA Mash nativersing	Antenna type *	internal
Fit AP mode features	Mesh networking	Weight & dimensions	
VLAN support	✓	Width	160 mm
Rate limiting	✓	Depth	160 mm
Flow control support	1	Height	33.6 mm
Band steering	1	Packaging data	
Airtime Fairness (ATF)	✓	Package type	Box
Quality of Service (QoS) support	✓	Packaging content	
BeamForming	✓	Quantity per pack	1 pc(s)
Transmitting power (CE)	27 dBm	Mounting kit	✓
Transmitting power (FCC)	22 dBm	Quick start guide	·
Security			-
Security algorithms *	HTTPS, SNMP, SNMPv2, SNMPv3,	Operational conditions	10 000/
, ,	SSH, WPA, WPA2, WPA3	Operating relative humidity (H-H)	10 - 90%
MAC address filtering	1	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
		Storage temperature (1-1) Storage relative humidity (H-H)	5 - 90%
		Storage relative numbers (H-H)	J - 90 /0









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.