



AOC E1 24E1Q PC lamekuvar 60,5 cm (23.8") 1920 x 1080 pikslit Full HD LED Must

Brand : AOC

Product family: E1

Product code: 24E1Q

Product name : 24E1Q

AOC E1 24E1Q. Ekraani diagonaal: 60,5 cm (23.8"), Ekraani resolutsioon: 1920 x 1080 pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LED, Ekraani pind: Matt, Reaktsiooniaeg: 5 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud kõlar(id). VESA paigaldamine. Toote värv: Must



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	On Screen Display (OSD)	✓
Display resolution *	1920 x 1080 pixels		Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
HD type *	Full HD	On Screen Display (OSD) languages	
Native aspect ratio *	16:9		
Display technology *	LED	Number of OSD languages	16
Panel type *	IPS		
Backlight type	W-LED		
Touchscreen *	✗		
Display brightness (typical)	250 cd/m ²		
Response time *	5 ms		
Display surface	Matt		
Screen shape *	Flat		
Supported graphics resolutions	1920 x 1080 (HD 1080)		
Supported video modes	1080p		
Aspect ratio	16:9		
Contrast ratio (typical) *	1000:1		
Contrast ratio (dynamic)	20000000:1		
Maximum refresh rate *	60 Hz		
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Display number of colours *	16.7 million colours		
Pixel pitch	0.2745 x 0.2745 mm		
Horizontal scan range	30 - 83 kHz		
Vertical scan range	50 - 76 Hz		
Viewable size, horizontal	52.7 cm		
Viewable size, vertical	29.6 cm		
Digital horizontal frequency	30 - 83 kHz		
Digital vertical frequency	50 - 76 Hz		
Display diagonal (metric)	60.452 cm		
Surface hardness	3H		
Colour depth	6 bit		
sRGB coverage (typical)	106%		
Adobe RGB coverage	78%		
Performance		Power	
NVIDIA G-SYNC *	✗	Energy efficiency class (SDR) *	E
Flicker-free technology	✓	Energy consumption (SDR) per 1000 hours *	19 kWh
Low Blue Light technology	✓	Power consumption (typical) *	20 W
		Power consumption (standby) *	0.5 W
		Power consumption (off)	0.5 W
		AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Energy efficiency scale	A to G
		European Product Registry for Energy Labelling (EPREL) code	388961
		External power adapter	✗
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-25 - 55 °C
		Operating relative humidity (H-H)	10 - 85%
		Storage relative humidity (H-H)	5 - 93%
		Operating altitude	0 - 5000 m
		Non-operating altitude	5000 - 12192 m
		Weight & dimensions	
		Width (with stand)	539.1 mm
		Depth (with stand)	199.4 mm
		Height (with stand)	404.9 mm
		Weight (with stand)	3.1 kg
		Width (without stand)	325.6 mm
		Depth (without stand)	49.6 mm
		Height (without stand)	539.1 mm
		Weight (without stand)	2.7 kg

Multimedia		Packaging data	
Number of speakers	2	Package width	609 mm
RMS rated power	2 W	Package depth	137 mm
Built-in speaker(s) *	✓	Package height	421 mm
Built-in microphone	✗	Package weight	4.7 kg
Design		Package type	Box
Market positioning *	Business	VGA cable length	1.8 m
Product colour *	Black	Packaging content	
Front bezel colour	Black	Cables included	AC, VGA
Detachable stand	✓	Audio cable length	1.8 m
Ports & interfaces		DisplayPort cable length	1.8 m
VGA (D-Sub) ports quantity	1	HDMI cable length	1.8 m
HDMI ports quantity	1	Power cable length	1.8 m
HDMI version	1.4	Sustainability	
DisplayPorts quantity	1	Doesn't contain	PVC/BFR
DisplayPort version	1.2	Other features	
Audio input	✓	Exterior finish type	Textured
Headphone out *	✓	Recyclable packaging material	100%
Headphone outputs	1	Heavy metals free	Hg (mercury)
Headphone connectivity	3.5 mm	Bezel thickness type	Frameless
Microphone in	✓	Compliance certificates	WEEE
Ergonomics		Mean time between failures (MTBF)	50000 h
VESA mounting *	✓	Light effects	✗
Panel mounting interface	100 x 100 mm	Certification	ISO 9241-307
Cable lock slot *	✗	Recycling data	
Height adjustment *	✗	Post-consumer recycled plastic	85%
Pivot	✗	Logistics data	
Tilt adjustment	✓	Harmonized System (HS) code	85285210
Tilt angle range	-3.5 - 21.5°		



4038986146234



0685417720682



685417720682

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.