

D-Link DUB-E250 võrgukaart Ethernet 2500 Mbit/s

Brand : D-Link

Product code: DUB-E250

Product name : DUB-E250

D-Link DUB-E250. Ühenduvustehnoloogia: Juhtmega ühendatud, Hostiliides: USB tüüp-C, Liides: Ethernet. Andmete edastamise maksimaalne määr: 2500 Mbit/s. Toide USB kaudu. Toote värv: Valge



Pesad & liidesed		Võimsus	
Ühenduvustehnoloogia *	Juhtmega ühendatud	Võimsustarve	250 mA
Hostiliides *	USB tüüp-C	Toide USB kaudu	✓
Liides *	Ethernet	Süsteeminõuded	
Ethernet LAN (RJ-45) pordid	1	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks	
USB versioon	2.0/3.2 Gen 1 (3.1 Gen 1)		
Võrgustumine			
Andmete edastamise maksimaalne määr *	2500 Mbit/s		
Võrgustandardid *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x		
Ethernet LAN	✓		
Ethernet-liidese tüüp	2.5 Gigabit Ethernet		
Ethernet LAN-i andmeedastuskiirused	10,100,1000,2500 Mbit/s		
Auto MDIX IEEE	✓		
Täisdupleks	✓		
VLAN sildistamine	✓		
Disain		Toetatud Maci operatsioonisüsteemid	
Toote värv	Valge		
Sisemine *	✗		
Hot-Plug tugi	✓		
Isehäälestuv	✓		
Sertifikaat	CE, FCC, IC		
		Töötingimused	
		Kasutamistemperatuur (T-T)	10 - 45 °C
		Hoiustamistemperatuur (T-T)	10 - 70 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 85 protsenti
		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
		Kaal ja mõõtmed	
		Laius	21,5 mm
		Sügavus	53 mm
		Kõrgus	15 mm
		Kaal	28,5 g

Logistika andmed

Harmonized System (HS) kood	85176990
-----------------------------	----------

Muud funktsioonid

Voo reguleerimise tugi	✓
Kaabli pikkus	0,16 m



0790069457494



790069457494



0790069457661



790069457661

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.