



TP-Link JetStream TL-SG3452X võrgulüliti Juhitav L2+ Gigabit Ethernet (10/100/1000) 1U Must

Brand : TP-Link

Product family: JetStream

Product code: TL-SG3452X

Product name : TL-SG3452X



TP-Link JetStream TL-SG3452X. Lüliti tüüp: Juhitav, Lüliti kiht: L2+. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 48, Konsooli port: RJ-45/Micro-USB. MAC-aadresside tabel: 16000 sisestust, Lülitusvõime: 176 Gbit/s. Võrgustandardid: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad. Toitepistik: Vahelduvvoolu sisendpesa. Püstikmontaaž, Toote kuju: 1U



Juhtimisfunktsioonid		Turvalisus	
Lüliti tüüp *	Juhitav	Tsükli kaitse	✓
Lüliti kiht	L2+	BPDU filtreerimine/kaitse	✓
Teenusekvaliteedi (QoS) tugi	✓	IP-MAC pordi sidumine	✓
Veebipõhine haldus	✓	Autentimine	Auto VLAN, Guest VLAN, MAC-põhine autentimine, Pordipõhine autentimine
Pilvepõhine haldus	✓	Salasõna kaitse	✓
APR-i ülevaatus	✓	Autentimise tüüp	AAA, RADIUS, TACACS+
Asukoha seadete konfigureerimine (CLI)	✓	Queue scheduling algorithms	SP, WRR+SP, Weighted Round Robin (WRR)
Süsteemisündmuste logi	✓		
MIB-tugi	RFC1213, RFC2233, RFC1643, RFC1493, RFC2674, RFC2819, RFC2021, RFC2620, RFC2618,		
Avalik MIB	✓		
Huawei-sisene MIB	✓		
Pesad & liidesed		Multisaate tunnused	
RJ-45 Etherneti ühenduse pesade arv *	48	Multiedastuse tugi	✓
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Multicast listener discovery (MLD) snoopimine	✓
SFP+ mooduli pesade arv	4		
Konsooli port	RJ-45/Micro-USB		
Toitepistik	Vahelduvvoolu sisendpesa		
Võrgustumine		Protokollid	
Võrgustandardid *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad	Haldusprotokollid	SNMPv1/v2c/v3, SNMP
10G-tugi *	✓	GARP VLAN Registration Protocol (GVRP)	✓
Pordipeegeldus	✓	IPv4 ja IPv6 elemendid	IPv4/IPv6 access-control list (ACL), IPv6 Telnet, IPv6 ping, IPv6 tracer
Voo reguleerimise tugi	✓		
Linkide koondamine	✓		
Levindamise tormi kontroll	✓		
Kiiruse piiramine	✓		
Geneeritava puu protokoll	✓		
HOL-blokeerimine	✓		
		Disain	
		Püstikmontaaž *	✓
		Toote kuju	1U
		Toote värv	Must
		LED-indikaatorid	✓
		Sertifikaat	CE, FCC, RoHS
		Võimsus	
		Toiteallikas *	Vahelduvvool
		Kaasas toiteplokk *	✓
		AC-sisendpinge	100 - 240 V
		AC-sisendsagedus	50/60 Hz
		Elektritarbimine (max)	32,72 W

Võrgustumine		Internet elektrivõrgu kaudu (PoE)	
IPv4 marsruudid	48	Power over Ethernet tugi *	✘
IPv6 marsruudid	48	Töötingimused	
VLAN-i tugi	✓	Kasutamistemperatuur (T-T)	0 - 45 °C
Virtuaalse LANi elemendid	Private VLAN, Tagged VLAN, VLAN mapping, Voice VLAN	Hoiustamistemperatuur (T-T)	-40 - 70 °C
VLAN-ide arv	4000	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Andmeedastus		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Lülitusvõime *	176 Gbit/s	Soojuse hajumine	111,65 BTU/h
Edastamise kiirus	130,9 Mpps	Kaal ja mõõtmed	
MAC-aadresside tabel *	16000 sisestust	Laius	440 mm
Staatiline ruutimine	✓	Sügavus	220 mm
Staatiliste marsruutide arv	48	Kõrgus	44 mm
Hiielkaadrite tugi	✓	Pakendi andmed	
Hiielkaadrite	9000	Kaablid kaasa arvatud	Vahelduvvool
Paketi puhvermälu	12 MB	Kiirstardi juhend	✓
Turvalisus		Raamisiin	✓
DHCP elemendid	DHCP client, DHCP relay, DHCP server	Pakendi laius	528 mm
Pääsuloend (ACL)	✓	Pakendi sügavus	336 mm
IGMP-jälgimine	✓	Pakendi kõrgus	100 mm
IGMP proxy	✓	Pakendi kaal	4 kg
MAC-aadresside filtreerimine	✓	Logistika andmed	
Staatilise pordi turvalisus	✓	Harmonized System (HS) kood	85176990
SSH/SSL tugi	✓		



0840030702501



840030702501



6935364006488

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.