

ASUS RT-AX1800U juhtmevaba ruuter Gigabit Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Must

Brand : ASUS

Product code: 90IG06P0-MO3520

Product name : RT-AX1800U

ASUS RT-AX1800U. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN edastuskiirus (max): 1201 Mbit/s. Ethernet LAN-liidese tüüp: Gigabit Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s, Kaabeldustehnoloogia: 10/100/1000Base-T(X). Turvaalgoritmid: WPA, WPA2-Enterprise, WPS. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Must, LED-indikaatorid: LAN, Võimsus, USB, WAN. Antenni kujundus: Väline



WAN connection		Security	
Ethernet WAN *	✓	Security algorithms	WPA, WPA2-Enterprise, WPS
DSL WAN *	✗	Firewall	✓
SIM card slot *	✗	Guest access	✓
3G/4G USB modem compatibility *	✗	Parental control	✓
Wireless LAN features		MAC address filtering	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	System event log	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	DMZ support	✓
WLAN data transfer rate (max) *	1201 Mbit/s	Protocols	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	DHCP server	✓
Network		Design	
Ethernet LAN *	✓	Product colour	Black
Ethernet LAN interface type *	Gigabit Ethernet	LED indicators	LAN, Power, USB, WAN
Ethernet LAN data rates	10,100,1000 Mbit/s	On/off switch	✓
Cabling technology	10/100/1000Base-T(X)	Product type *	Tabletop router
Port triggering	✓	Antenna	
Dynamic DNS (DDNS)	✓	Antenna design *	External
VPN support	- VPN Client L2PT - VPN Client OVPN - VPN Client PPTP - VPN Server IPsec - VPN Server OVPN - VPN Server PPTP	Antennas quantity	4
Mobile network		Features	
3G	✗	Internal memory	256 MB
4G	✗	Flash memory	128 MB
5G	✗	Works with Amazon Alexa	✓
		Power	
		Power source type *	DC
		AC input voltage	110 - 240 V
		AC input frequency	50 - 60 Hz

Ports & interfaces		Power	
Ethernet LAN (RJ-45) ports *	3	Output voltage	12 V
USB port *	✓	Output current	1.5 A
USB 2.0 ports quantity	1	Weight & dimensions	
DC-in jack	✓	Width	190 mm
Management features		Depth	126 mm
Bandwidth control	✓	Height	45 mm
Quality of Service (QoS) support	✓	Weight	346 g
Wake-on-LAN ready	✓	Packaging data	
Reset button	✓	Package width	305 mm
WPS push button	✓	Package depth	126 mm
MU-MIMO technology	✓	Package height	45 mm
MIMO	✓	Package weight	1.28 kg
		Package type	Box
		Logistics data	
		Harmonized System (HS) code	85176990



4711081542506

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-JAN-2025. Prints or copies of Information are only valid on the printed Publication date