## KYOCERA ECOSYS M2635dn Laser A4 1200 x 1200 DPI 35 lk/min

Brand: KYOCERA Product family: ECOSYS Product code: 1102S13NL0

Product name: M2635dn

KYOCERA ECOSYS M2635dn. Printimistehnoloogia: Laser, Printimine: Mono printimine, Maksimaalne resolutsioon: 1200 x 1200 DPI. Kopeerimine: Mono kopeerimine, Maksimaalne kopeerimisresolutsioon: 600 x 600 DPI. Skaneerimine: Värviskaneerimine, Optilise skaneerimise resolutsioon: 600 x 600 DPI. Faksimine: Mono faksimine. Dupleksfunktsioonid: Print. Maksimaalne ISO A-seeria paberi suurus: A4. Otseprintimine. Toote värv: Must, Valge





Printing		Paper handling	
Duplex printing mode Print technology *	Auto Laser	Multi-Purpose Tray media weight Duplex media weight	60 - 220 g/m² 60 - 163 g/m²
Printing *	Mono printing	Ports & interfaces	
Duplex printing *  Maximum resolution *  Print speed (black, normal quality, A4/US Letter) *	1200 x 1200 DPI 35 ppm	Standard interfaces Direct printing * USB port	Ethernet, USB 2.0
Duplex print speed (black, normal quality, A4/US Letter)	17.5 ppm	USB 2.0 ports quantity	2
Warm-up time Time to first page (black, normal) N-in-1 print function Tray priority settings function N-up printing Barcode printing Watermark printing Secure printing Booklet printing function	17 s 6.8 s	Network  Wi-Fi * Ethernet LAN * Cabling technology Ethernet LAN data rates Bluetooth Near Field Communication (NFC)  Mobile printing technologies	X  ✓ 10/100/1000Base-T(X) 10,100,1000 Mbit/s  X  Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Poster printing function	✓	Performance	
Borderless printing	×	Maximum internal memory	1536 MB
Copying		Card reader integrated Internal memory *	✓ 512 MB
Duplex copying * Copying *	X Mono copying	Compatible memory cards	SD, SDHC

Camadan		Daufauman a	
Copying		Performance	
Maximum copy resolution *	600 x 600 DPI	Built-in processor	<b>√</b>
Copy speed (black, normal quality, A4)	35 cpm	Processor family	ARM Cortex-A9
Time to first copy (black, normal)	6.9 s	Processor frequency	800 MHz
Maximum number of copies	999 copies	Sound pressure level (printing)	51 dB 51 dB
Copier resize	25 - 400%	Sound pressure level (copying) Sound pressure level (quiet mode)	47 dB
N-in-1 copy function	✓	Sound power level (standby)	29 dB
N-in-1 copy function (N=)	2, 4		25 0.5
Copy programming function	✓	Design	
ID-card copy function	✓	Product colour *	Black, White
Scanning		Market positioning *	Business
		Built-in display *	•
Duplex scanning *	×	Display	LCD
Scanning *	Colour scanning	Display number of lines	5 lines
Optical scanning resolution * Scan technology	600 x 600 DPI CIS	Power	
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Power consumption (average	661 W
Scan speed (colour)	23 ppm	operating)	
Scan speed (black)	40 ppm	Power consumption (printing)	661 W
Image formats supported	JPEG, TIF	Power consumption (copying)  Power consumption (ready)	661 W 21 W
Document formats supported	PDF, XPS	Power consumption (ready)	1 W
Scan drivers	TWAIN, WIA	Energy Star Typical Electricity	
Fax		Consumption (TEC)	1.47 kWh/week
		AC input voltage	220 - 240 V
Duplex faxing	×	AC input frequency	50 - 60 Hz
Faxing *	Mono faxing	System requirements	
Fax resolution (black)	400 x 400 DPI	Windows operating systems	
Fax transmission speed Modem speed	3 sec/page 33.6 Kbit/s	supported	<b>✓</b>
Fax coding methods	JBIG, MH, MMR, MR		Mac OS X 10.10 Yosemite, Mac OS X
	joio, inii, iniiii, inii		10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
Features			Mac OS X 10.14 Mojave, Mac OS X
Recommended duty cycle	1000 - 2500 pages per month	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5
Recommended duty cycle Maximum duty cycle *	20000 pages per month	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X
Recommended duty cycle Maximum duty cycle * Duplex functions *	20000 pages per month Print	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender	20000 pages per month		Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges *	20000 pages per month Print  1	Mac operating systems supported  Linux operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender	20000 pages per month Print  1 Black		Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges *	20000 pages per month Print  1	Linux operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours *	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL	Linux operating systems supported  Operational conditions	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H)  Storage temperature (T-T)  Operating temperature (T-T)	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H)  Storage temperature (T-T)  Operating temperature (T-T)  Storage relative humidity (H-H)	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90%
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H)  Storage temperature (T-T)  Operating temperature (T-T)  Storage relative humidity (H-H)  Operating altitude	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays *	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H)  Storage temperature (T-T)  Operating temperature (T-T)  Storage relative humidity (H-H)	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90%
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity *	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H)  Storage temperature (T-T)  Operating temperature (T-T)  Storage relative humidity (H-H)  Operating altitude	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity *	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks ✓  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks ✓  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets 100 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability  Sustainability certificates	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m  GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets 3	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability  Sustainability certificates	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m  GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets 3 850 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability  Sustainability certificates  Weight & dimensions  Width Depth	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR  417 mm 412 mm
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF) Maximum number of input trays Maximum input capacity Maximum input capacity Maximum output capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets 3	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m  GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR  417 mm 412 mm 437 mm
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum number of input trays Maximum input capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets 3 850 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability  Sustainability certificates  Weight & dimensions  Width Depth	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR  417 mm 412 mm
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF) Maximum number of input trays Maximum input capacity Maximum input capacity Maximum output capacity	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets 3 850 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m  GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR  417 mm 412 mm 437 mm
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF) Maximum number of input trays Maximum input capacity Maximum input capacity Paper handling Maximum ISO A-series paper size * Maximum print size	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  ✓ 100 sheets Cassette, Paper tray  ✓ 50 sheets 3 850 sheets 150 sheets  A4 216 x 356 mm	Linux operating systems supported  Operational conditions Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability  Sustainability certificates  Weight & dimensions  Width Depth Height Height Weight	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m  GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR  417 mm 412 mm 437 mm
Recommended duty cycle Maximum duty cycle * Duplex functions * Digital sender Number of print cartridges * Printing colours * Page description languages Number of printer fonts Replacement cartridges Input & output capacity Total number of input trays * Total input capacity * Total output capacity * Paper tray 1 input capacity Multi-Purpose tray Multi-Purpose tray Multi-Purpose tray input capacity Paper input type Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF) Auto document feeder (ADF) Maximum number of input trays Maximum input capacity Maximum output capacity Paper handling Maximum ISO A-series paper size *	20000 pages per month Print  1 Black Microsoft XPS, PCL 5e, PCL 6, PCL XL, PostScript 3 93 TK-1150 (3.000 pagina's)  1 250 sheets 150 sheets 250 sheets  100 sheets Cassette, Paper tray  50 sheets 3 850 sheets 150 sheets 150 sheets	Linux operating systems supported  Operational conditions  Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Certificates  Waste Electrical and Electronic Equipment (WEEE) compliance Certification  Sustainability Sustainability certificates  Weight & dimensions  Width Depth Height Weight  Packaging data	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks  10 - 80% -20 - 40 °C 10 - 32.5 °C 10 - 90% 0 - 3500 m 0.6 - 15000 m   GS, TÜV, CE, ISO 9001, ISO 14001  Blue Angel, EPEAT Silver, ENERGY STAR  417 mm 412 mm 437 mm 19 kg

Paper handling		Packaging data	
ISO B-series sizes (B0B9) Non-ISO print media sizes Custom media width Custom media length Paper tray media weight	B5, B6 Legal, Letter 70 - 216 mm 148 - 356 mm 60 - 163 g/m <sup>2</sup>	Package height Package weight	572 mm 25 kg
		Packaging content	
		Cartridge(s) included Included cartridge capacity (black) Imaging unit included Cables included Logistics data	✓ 1000 pages ✓ AC
		Harmonized System (HS) code	84433100
		Technical details  Compliance certificates	REACH, RoHS
		Other features	NEACH, NOTS
		Cartridge type	TK-1150





632983040270

0632983040270

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.