Canon

Canon EOS R50 Mirrorless Camera Content Creator Kit MILC (Peeglita vahetatavate objektiividega kaamera) 24,2 MP CMOS 6000 x 4000 pikslit Must

Brand : Canon   **Product family:** EOS   **Product code:** 5811C035

Product name : EOS R50 Mirrorless Camera Content Creator Kit

Canon EOS R50 Mirrorless Camera Content Creator Kit. Kaamera tüüp: MILC (Peeglita vahetatavate objektiividega kaamera), Megapiksel: 24,2 MP, Anduri tüüp: CMOS, Maksimaalne pildiresolutsioon: 6000 x 4000 pikslit. ISO-tundlikkus (max): 51200. Fookuskauguse ulatus: 18 - 45 mm. Kaamera kiireim katikukiirus: 1/8000 s. WiFi. HD tüüp: 4K Ultra HD, Maksimaalne video resolutsioon: 3840 x 2160 pikslit. Puutetundlik ekraan. Pildiotsija tüüp: Elektrooniline. PictBridge. Kaal: 328 g. Toote värv: Must

Picture quality

Image sensor aspect ratio	3:2
Camera type *	MILC
Megapixel (approx.) *	24.2 MP
Sensor type *	CMOS
Maximum image resolution *	6000 x 4000 pixels
Still image resolution(s) *	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600
Image stabilizer *	✘
Supported aspect ratios	1:1, 3:2, 4:3, 16:9
Image sensor size (W x H)	22.3 x 14.9 mm
Sensor format	Advanced Photo System type-C (APS-C)
Built-in low-pass filter	✔
Image formats supported *	JPEG, RAW, C-RAW, HEIF

Lens system

Focal length range	18 - 45 mm
Minimum focal length (35mm film equiv)	29 mm
Maximum focal length (35mm film equiv)	72 mm
Minimum aperture number	32
Maximum aperture number	4.5
Lens structure (elements/groups)	7/7
Lens type	Standard zoom
Filter size	49 mm
Number of diaphragm blades	7
Lens mount interface	Canon RF

Focusing

Focus *	TTL
Focus adjustment *	Auto/Manual
Auto focusing (AF) modes *	Continuous Auto Focus, One Shot Focus, Servo Auto Focus

Display

Display diagonal (metric)	7.5 cm
Display resolution	1620000 dot
Display aspect ratio	3:2
Vari-angle LCD display	✔

Viewfinder

Viewfinder type	Electronic
Magnification	0.95x
Viewfinder screen size	0.39"
Viewfinder frame rate (power saving mode)	60 fps
Viewfinder frame rate (smooth mode)	120 fps
Viewfinder resolution (approx.)	2360000 pixels

Ports & interfaces

PictBridge *	✔
USB version *	2.0
USB connector	USB Type-C
HDMI *	✔
HDMI version	2.0
HDMI connector type	Micro
Microphone in	✔

Network

Bluetooth *	✔
Bluetooth version	4.2
Bluetooth Low Energy (BLE)	✔
Wi-Fi *	✔
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)

Camera

White balance *	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Shade, Tungsten

Focusing

Auto Focus (AF) object detection	Animal, Bird, CAT, Dog, People, Vehicle
Face tracking	✔
Auto Focus (AF) lock	✔
Auto Focus (AF) assist beam	✔

Exposure

ISO sensitivity (min) *	100
ISO sensitivity (max) *	51200
ISO sensitivity	100, 6400, 25600, 51200
Light exposure modes *	Aperture priority AE, Auto, Manual, Shutter priority AE
Light exposure control	Program AE
Light exposure correction *	± 3EV (1/3EV step)
Light metering *	Centre-weighted, Evaluative (Multi-pattern), Partial, Spot
Auto Exposure (AE) lock	✔
Number of measurement zones	384
Exposure bracketing (AEB)	± 3EV (1/2EV; 1/3EV stop)
Anti-flicker shooting	✔

Shutter

Fastest camera shutter speed *	1/8000 s
Slowest camera shutter speed *	30 s
Camera shutter type	Electronic

Flash

Flash exposure lock	✔
Flash guide number	6 m
External flash connector	✔
Flash exposure compensation	✔
Flash exposure correction	±3EV (1/3 EV step)
Shoe mounting point	✔

Video

Video recording *	✔
Maximum video resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Video resolutions	1920 x 1080,3840 x 2160 pixels
Video formats supported	H.264, H.265
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit

Audio

Built-in microphone *	✔
Built-in speaker(s)	✔
Audio system	stereo
Wind filter	✔
Audio formats supported	LPCM, AAC

Memory

Compatible memory cards *	SD, SDHC, SDXC
Memory slots	1

Display

Display *	LCD
Touchscreen *	✔

Camera

Scene modes *	Children, Close-up (macro), Food, Group photo, HDR backlight control, Handheld night scene, Landscape, Panning, Panorama, Portrait, Self-portrait, Silent shutter, Smooth skin, Sports
Shooting modes *	Aperture priority, Auto, Intelligent auto, Manual, Program, Scene, Shutter priority
Self-timer delay *	2,10 s
Dioptre correction	✔
Diopter adjustment (D-D)	-3 - 1
Histogram	✔
Live view	✔
Direct printing	✔
GPS (satellite)	✘
Orientation sensor	✔
Anti-dust function	✘
Smartphone/tablet remote support	✔
View on smartphone	✔
Playback zoom (min)	1.5x
Playback zoom number of steps	15
Erase protection options	Folder, Memory card, Single image
Tripod mounting supported *	✔
Slideshow	✔
Image processor	DIGIC X

Design

Product colour *	Black
Dustproof	✘
Splash proof	✘

Battery

Battery technology *	Lithium-Ion (Li-Ion)
Battery type	LP-E17
Number of batteries supported	1
Battery level indicator	✔
Battery level indicator number of levels	4

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Weight & dimensions

Width	116.3 mm
Depth	68.8 mm
Height	85.5 mm
Weight	328 g
Weight (including battery)	375 g
Lens weight	130 g

Packaging content

Wrist strap included	✔
Battery charger included	✔
Batteries included	✔
Remote control included	✔
Carrying case	✔
Lens cap included	✔

Logistics data

Products per pallet	120 pc(s)

8714574676050