

ASUS ROG Rapture GT6 Kolm sagedusala (2,4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Valge 4 Sisemodem

Brand : ASUS

Product code: 90IG07F0-MU9A30

Product name : ROG Rapture GT6

ASUS ROG Rapture GT6. Toote värv: Valge, Antenni tüüp: Sisemodem, Toote tüüp: Võrguruuter. Wi-Fi laineala: Kolm sagedusala (2,4 GHz / 5 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WiFi-standardid: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Protsessori sagedus: 1,7 GHz, Sisemälu: 512 MB, Välmälu: 256 MB. AC-adaptori sisendpinge: 110 - 240 V, AC-adaptori sagedus: 50 - 60 Hz, AC-adaptori väljundpinge: 19 V. Laius: 172,3 mm, Sügavus: 78,1 mm, Kõrgus: 176,8 mm



Disain		Funktsioonid	
Toote tüüp	Võrguruuter	Protsessori sagedus	1,7 GHz
Toote värv *	Valge	Sisemälu	512 MB
LED-indikaatorid	Võimsus	Välmälu	256 MB
Antenni tüüp *	Sisemodem	Teenusekvaliteedi (QoS) tugi	✓
Antennide arv	9	BeamForming	✓
Maksimaalne katvus	538,8 m ²	Vanemlik kontroll	✓
Lähtestusnupp	✓	SSID-levi	✓
Juhtmevaba LAN-i omadused		Tehnoloogia MU-MIMO	✓
Wi-Fi laineala *	Kolm sagedusala (2,4 GHz / 5 GHz / 5 GHz)	Protokollid	
Wi-Fi standard *	Wi-Fi 6 (802.11ax)	DHCP-server	✓
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Pesad & liidesed	
WLAN edastuskiirus (esimene laineala)	574 Mbit/s	Ethernet LAN (RJ-45) pordid *	4
WLAN edastuskiirus (teine laineala)	4804 Mbit/s	Ethernet WAN	✓
WLAN andmeedastuskiirus (kolmas laineala)	4804 Mbit/s	DC-pistik	✓
Võrgustandardid	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Võimsus	
Turvaalgoritmid	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3	AC-adaptori sisendpinge	110 - 240 V
Point-to-point protocol over Ethernet (PPPoE)	✓	AC-adaptori sagedus	50 - 60 Hz
IGMP-jälgimine	✓	AC-adaptori väljundpinge	19 V
Dünaamiline DNS (DDNS)	✓	AC-adaptori väljundvool	2,37 A
VPN-tugi	VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Client WireGuard VPN Server IPSec VPN Server OVPN VPN Server PPTP VPN Server WireGuard VPN Fusion	Kaal ja mõõtmed	
Funktsioonid		Laius	172,3 mm
Sisesehitatud protsessor	✓	Sügavus	78,1 mm
Protsessorituumad	3	Kõrgus	176,8 mm
		Kaal	880 g
		Pakendi laius	425 mm
		Pakendi sügavus	280 mm
		Pakendi kõrgus	140 mm
		Pakendi kaal	4,16 kg
		Pakendi sisu	
		Kaasnevate toodete arv	1 tk

Pakendi sisu

Ethernet-kaabel





4711081798576

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date