

NETGEAR GS728TP Juhitav L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Hall

Brand : NETGEAR

Product code: GS728TP-300EUS

Product name : GS728TP



NETGEAR GS728TP. Lüliti tüüp: Juhitav, Lüliti kiht: L2/L3/L4. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 24, Installitud SFP moodulite hulk: 4. MAC-aadresside tabel: 16000 sisestust, Lülitusvõime: 56 Gbit/s. Võrgustandardid: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Power over Ethernet tugi. Püstikmontaaž



Juhtimisfunktsioonid		Disain	
Lüliti tüüp *	Juhitav	Lisaventilaatorite võimalus	✓
Lüliti kiht	L2/L3/L4	Ventilaatorite arv	2 ventilaator(id)
APR-i ülevaatus	✓	Sertifikaat	CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA
Pesad & liidesed		Toimimine	
RJ-45 Etherneti ühenduse pesade arv *	24	Sisseehitatud protsessor	✓
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Protsessori tootja	ARM
Installitud SFP moodulite hulk *	4	Protsessori mudel	ARM Cortex-A55
USB tüüp A portide arv	1	Protsessori sagedus	800 MHz
Võrgustumine		Sisemälu	512 MB
Võrgustandardid *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x	Välkmälu	64 MB
Pordipeegeldus	✓	Müratase	26,8 dB
IPv4 marsruudid	32	Keskmine tõrkeintervall (MTBF)	1751613 h
IPv6 marsruudid	32	Võimsus	
VLAN-i tugi	✓	Toiteallikas *	Vahelduvvool
VLAN-ide arv	256	Võimsustarve (tüüpiline)	24 W
Andmeedastus		Elektritarbimine (max)	226 W
Lülitusvõime *	56 Gbit/s	Internet elektrivõrgu kaudu (PoE)	
MAC-aadresside tabel *	16000 sisestust	Power over Ethernet tugi *	✓
Latentsus (10-100 Mbit/s)	8,864 µs	Toide üle võrgu (PoE) pesade arv	24
Paketi puhvermälu	1,5 MB	Toide üle võrgu (PoE) võimsus pordi kohta	190 W
Turvalisus		Töötingimused	
DHCP elemendid	DHCP snooping, DHCPv6 client	Kasutamistemperatuur (T-T)	0 - 50 °C
Pääsuloend (ACL)	✓	Hoiustamistemperatuur (T-T)	-20 - 70 °C
Access Control List (ACL) IPv4 sissekanded	100	Suhteline õhuniiskus kasutamisel (H-H)	0 - 90 protsenti
Multisaate tunnused		Suhteline õhuniiskus (H-H) hoiustamisel	0 - 95 protsenti
Multiedastuse tugi	✓	Soojuse hajumine	772,9 BTU/h
Filtreeritud multisaate gruppide arv	512	Kaal ja mõõtmed	
Disain		Laius	440 mm
Püstikmontaaž *	✓	Sügavus	257 mm
		Kõrgus	432 mm
		Kaal	3,78 kg

Disain

Toote värv

Hall



0606449162257



606449162257

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date