



TP-Link Archer AX12 juhtmevaba ruuter Kiire Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Must

Brand : TP-Link

Product family: Archer

Product code: ARCHER AX12

Product name : Archer AX12

TP-Link Archer AX12. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN edastuskiirus (max): 1501 Mbit/s. Ethernet LAN-liidese tüüp: Kiire Ethernet, Võrgustandardid: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Turvaalgoritmid: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3. Toote tüüp: Laua peale asetatav ruuter, Toote värv: Must. Antenni kujundus: Väline



WAN-ühendus		Turvalisus	
Ethernet WAN *	✓	Tulemüür	✓
DSL WAN *	✗	URL-i filtreerimine	✓
SIM kaardi ava *	✗	DMZ-tugi	✓
3G/4G USB modemi ühilduvus *	✗	Protokollid	
Juhtmevaba LAN-i omadused		Universaalne Plug and Play (UPnP)	✓
Wi-Fi laineala *	Kaks sagedusala (2,4 GHz / 5 GHz)	Disain	
Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Toote värv	Must
WLAN edastuskiirus (max) *	1501 Mbit/s	Toote tüüp *	Laua peale asetatav ruuter
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Pakendi sisu	
WLAN edastuskiirus (esimene laineala)	300 Mbit/s	Kiirpaigaldusjuhend	✓
WLAN edastuskiirus (teine laineala)	1201 Mbit/s	Antenn	
Võrgustumine		Antenni kujundus *	Väline
Ethernet LAN *	✓	Antennide arv	4
Ethernet LAN-liidese tüüp *	Kiire Ethernet	Võimsus	
Võrgustandardid	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Toiteallika tüüp *	Vahelduvvool
Portide suunamine	✓	Töötingimused	
Pordi aktiveerimine	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Dünaamiline DNS (DDNS)	✓	Hoiustamistemperatuur (T-T)	-40 - 60 °C
Pesad & liidised		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Ethernet LAN (RJ-45) pordid *	4	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
USB port *	✗	Kaal ja mõõtmed	
Juhtimisfunktsioonid		Laius	215 mm
Teenusekvaliteedi (QoS) tugi	✓	Sügavus	117 mm
Lähtestusnupp	✓	Kõrgus	32 mm
Turvalisus		Tehnilised andmed	
Turvaalgoritmid	WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3	Vastavussertifikaadid	CE, Föderaalne kommunikatsioonikomisjon (FCC), RoHS



4895252500875



4895252500882

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date