

## Dahua Technology ASR2100A-D Tavalise sissepääsuga pääsukontrolliluger Must

Brand : Dahua Technology Product code: DHI-ASR2100A-D

Product name: ASR2100A-D

Dahua Technology ASR2100A-D. Võimsustarve (tüüpiline): 1,7 W, DC-pingevahemik: 12 V, Alalisvool (max): 0,5 A. Laius: 123 mm, Sügavus: 86 mm, Kõrgus: 15 mm. Pakendi laius: 578 mm, Pakendi

sügavus: 383 mm, Pakendi kõrgus: 349 mm



Technical details		Camera	
Type *	Basic access control reader Access chip/card	Front camera *	×
Authentication type *		Ports & interfaces	
Buzzer		RS-485 ports	1
Wiegand interface		Power	
Tamper protection			1.7.14
Fingerprint reader *		Power consumption (typical) DC voltage range DC current (max)	1.7 W 12 V 0.5 A
Access chip/card reader *	<b>✓</b>		
Access chip/card reader type	Contactless	. ,	0.3 A
Contacting working distance	0 mm	Weight & dimensions	
Contactless working distance	5 cm	Width	123 mm
Verification (1:1) time	0.1 s	Depth	86 mm
Recommended usage	Indoor & outdoor	Height	15 mm
Unlock function	✓	Packaging data	
Active tampering alarm	✓	Package width	578 mm
Compliance certificates	CE, Federal Communications	Package depth	383 mm
Paraduset and accom	Commission (FCC)	Package height	349 mm
Product colour	Black	Package weight	350 g
Housing material	Acrylic, Polycarbonate (PC)	Operational conditions	
International Protection (IP) code	IP66	Operating temperature (T-T)	-30 - 70 °C
Display		Operating relative humidity (H-H)	5 - 95%
Built-in display *	×	Sustainability	
		Sustainability compliance	✓

