



Dahua Technology DHI-NVR5864-EI võrguvideosalvesti (NVR) Must

Brand : Dahua Technology

Product code: DHI-NVR5864-EI

Product name : DHI-NVR5864-EI



Dahua Technology DHI-NVR5864-EI. Video sisendkanalid: 64 kanalid, Maksimalne resolutsioon: 3840 x 2160 pikslit, Videosalvestusrežiimid: 1080p. Maksimalne salvestusmaht: 128 TB, Kõvaketta liides: SATA, RAID-tasemed: 0, 1, 5, 6, 10. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s, Toetatud võrguprotokollid: HTTP; HTTPS; TCP/IP; IPv4/IPv6; UDP; SNMP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; PPPoE; FTP;.... Toote värv: Must. AC-sisendpinge: 100 - 240 V, AC-sisendsagedus: 50 - 60 Hz

Toimimine		Pesad & liidesed	
Video sisendkanalid *	64 kanalid	RS-232 portide arv	1
Sisendkanali häire	16		HTTP; HTTPS; TCP/IP; IPv4/IPv6; UDP; SNMP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; PPPoE; FTP; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); Multicast; P2P; Auto Registration; iSCSI
Väljundkanali häire	8	Toetatud võrguprotokollid	
Videosalvestusrežiimid	1080p		
Maksimalne resolutsioon *	3840 x 2160 pikslit		
Toetatud resolutsioonid	3840 x 2160, 1920 x 1080, 1280 x 1024, 1280 x 720		
Installitud operatsioonisüsteem	Kaasas LINUX	Funktsioonid	
Varundamise funktsioon	✓	Püstikmontaaž	✓
Juhtmevaba LAN-i omadused		Toote värv	Must
WiFi *	✗	Protsessor	
Kõvaketas		Sisesehitatud protsessor	✓
Toetatud kõvaketaste arv	8	Võimsus	
Maksimalne salvestusmaht *	128 TB	AC-sisendpinge	100 - 240 V
Kõvaketta liides *	SATA	AC-sisendsagedus	50 - 60 Hz
RAID-tugi	✓	Süsteeminõuded	
RAID-tasemed	0, 1, 5, 6, 10	Toetatud mobiilsed operatsioonisüsteemid	Android, iOS
Pesad & liidesed		Brauseritugi	Chrome;IE;Safari;Edge;Firefox
Ethernet LAN (RJ-45) pordid *	2	Töötingimused	
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s	Kasutamistemperatuur (T-T)	-10 - 55 °C
HDMI-portide arv	2	Suhteline õhuniiskus kasutamisel (H-H)	10 - 93 protsenti
VGA (D-Sub) väljundpordid	2	Hoiustamistemperatuur (T-T)	-20 - 60 °C
USB 2.0 portide arv	2	Kaal ja mõõtmed	
USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk	2	Laius	439,9 mm
RS-485 pordid	2	Sügavus	457,9 mm
		Kõrgus	89 mm
		Kaal	6,4 kg
		Pakendi laius	570 mm
		Pakendi sügavus	570 mm
		Pakendi kõrgus	226 mm
		Pakendi kaal	9,01 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-AUG-2024. Prints or copies of Information are only valid on the printed Publication date