



## TP-Link JetStream TL-SG3452XP võrgulüliti Juhitav L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet tugi 1U Must

**Brand :** TP-Link

**Product family:** JetStream

**Product code:** TL-SG3452XP

**Product name :** TL-SG3452XP



TP-Link JetStream TL-SG3452XP. Lüliti tüüp: Juhitav, Lüliti kiht: L2+. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 48, Konsooli port: RJ-45/Micro-USB. MAC-aadresside tabel: 16000 sisestust, Lülitusvõime: 176 Gbit/s. Võrgustandardid: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE....  
Toitepistik: Vahelduvvoolu sisendpesa. Power over Ethernet tugi. Püstikmontaaž, Toote kuju: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2+	<b>Design</b>	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Form factor	1U
Cloud-managed	✓	Product colour	Black
ARP inspection	✓	Reset button	✓
Configuring Location Settings (CLI)	✓	LED indicators	✓
System event log	✓	Number of fans	3 fan(s)
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	48	Power source *	AC
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included *	✓
SFP+ module slots quantity	4	AC input voltage	100 - 240 V
Console port	RJ-45/Micro-USB	AC input frequency	50/60 Hz
Power connector	AC-in jack	Power consumption (max)	635.7 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z	Power over Ethernet (PoE) *	✓
	10G support *	Power over Ethernet plus (PoE+) ports quantity	48
Port mirroring	✓	Power over Ethernet (PoE) power per port	30 W
Flow control support	✓	Total Power over Ethernet (PoE) budget	500 W
Link aggregation	✓	Operational conditions	
Broadcast storm control	✓	Operating temperature (T-T)	0 - 40 °C
Rate limiting	✓	Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%

<b>Network</b>		<b>Operational conditions</b>	
Spanning tree protocol	✓	Heat dissipation	2169.2 BTU/h
Head-of-line (HOL) blocking	✓	<b>Weight &amp; dimensions</b>	
VLAN support	✓	Width	440 mm
<b>Data transmission</b>		Depth	330 mm
Switching capacity *	176 Gbit/s	Height	44 mm
Forwarding rate	130.9 Mpps	<b>Packaging content</b>	
MAC address table *	16000 entries	Cables included	AC
Store-and-forward	✓	Quick start guide	✓
Jumbo frames support	✓	<b>Packaging data</b>	
Jumbo frames	9000	Package width	440 mm
Packet buffer memory	12 MB	Package depth	528 mm
<b>Security</b>		Package height	100 mm
DHCP features	DHCP client, DHCP relay, DHCP server	Package weight	6.48 kg
Access Control List (ACL)	✓	<b>Certificates</b>	
IGMP snooping	✓	Certification	CE, FCC, RoHS
MAC address filtering	✓	<b>Logistics data</b>	
Static port security	✓	Harmonized System (HS) code	85176990
SSH/SSL support	✓		
BPDU filtering/protection	✓		
IP-MAC-Port binding	✓		
Authentication	Auto VLAN, Guest VLAN		



0840030702518



840030702518



6935364006501

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.