

MSI PRO B650M-P emaplaat AMD B650 Protsessoripesa AM5 Mikro ATX

Brand : MSI

Product code: PRO B650M-P

Product name : PRO B650M-P



MSI PRO B650M-P. Protsessori tootja: AMD, Protsessori pesa: Protsessoripesa AM5, Ühilduvad protsessoriseeriad: AMD Ryzen 7 7th Gen, AMD Ryzen 9 7th Gen. Toetatud mälutüübid: DDR5-SDRAM, Maksimaalne sisemälu: 192 GB, Toetatud mälu taksagedused: 6000, 5800, 5600, 5400, 5200, 5000, 4800 MHz. Kõvaketta ühenduse tüüp: M.2, SATA, RAID-tasemed: 0, 1, 10. Ethernet-liidese tüüp: 2.5 Gigabit Ethernet, LAN-kontroller: Realtek RTL8125-BG. Komponent: PC, Emaplaadi kujutegur: Mikro ATX, Emaplaadi kiibistik: AMD

Protsessor		Tagapaneeli I/O pesad	
Protsessori tootja *	AMD	HDMI-versioon	2.1
Protsessori pesa *	Protsessoripesa AM5	DisplayPort arv	1
Ühilduvad protsessoriseeriad *	AMD Ryzen 7 7th Gen, AMD Ryzen 9 7th Gen	DisplayPort versioon	1.4
Toetatud protsessoripesad	Protsessoripesa AM5	Kõrvaklapiväljundite arv	1
		Sisendkanal	✓
		Mikrofonisisend	✓
Mälu		Võrgustumine	
Toetatud mälutüübid *	DDR5-SDRAM	Ethernet LAN	✓
Mälukaardi pesade arv *	4	Ethernet-liidese tüüp	2.5 Gigabit Ethernet
Toetatud mälu taksagedused	6000, 5800, 5600, 5400, 5200, 5000, 4800 MHz	LAN-kontroller	Realtek RTL8125-BG
Maksimaalne sisemälu *	192 GB	WiFi *	✗
Ladustamise kontrollid		Funktsioonid	
Kõvaketta ühenduse tüüp *	M.2, SATA	Emaplaadi kiip *	AMD B650
RAID-tasemed	0, 1, 10	Helikiip	Realtek ALC897
		Audioväljundi kanalid *	7.1 kanalid
		PC tervise monitoorimine	Ventilaator
		Komponent *	PC
		Emaplaadi kujutegur *	Mikro ATX
		Emaplaadi kiibistik *	AMD
		Toetatud Windowsi operatsioonisüsteemid	Windows 11 x64
Sisemine I/O moodul		Laienduspesad	
USB 2.0 pistmikud *	4	PCI Expressi x16 (Gen 3.x) pesad	1
USB 3.2 Gen 1 (3.1 Gen 1) pistmikud *	2	M.2 (M) siinide arv	2
USB 3.2 Gen 2 (3.1 Gen 2) konnektorid *	1		
Esipaneeli audiopistik	✓		
Esipaneeli konnektor	✓		
ATX-toitepistik (24 kontakti)	✓		
CPU-ventilaatori pistmik	✓		
Keresse sissetungi pistmik	✓		
Tagapaneeli I/O pesad		BIOS	
USB 2.0 portide arv *	4	BIOS-i tüüp *	UEFI AMI
USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk *	2	BIOS-i mälu suurus	256 Mbit
USB 3.2 Gen 2 (3.1 Gen 2) A-tüüpi portide hulk *	2	ACPI versioon	6.4
Ethernet LAN (RJ-45) pordid *	1	System management BIOS (SMBIOS) versioon	3.5
VGA (D-Sub) portide arv *	1		
HDMI-portide arv *	1		
		Kaal ja mõõtmed	
		Laius	243,8 mm
		Sügavus	243,8 mm



4711377100953

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-AUG-2024. Prints or copies of Information are only valid on the printed Publication date