



QNAP TS-864EU-RP-8G võrkupääsu- ja varundusserver NAS Püstik (2U) Intel® Celeron® N5095 8 GB DDR4 0 TB QNAP Turbo System Must



Brand : QNAP

Product code: TS-864EU-RP-8G

Product name : TS-864EU-RP-8G

QNAP TS-864EU-RP-8G. Tüüp: NAS. Keretüüp: Püstik (2U). Seadme klass: Väike ja keskmise suurusega ettevõtte. Protsessori perekond: Intel® Celeron®, Protsessori mudel: N5095. Sisemälu: 8 GB, Sisemälu tüüp: DDR4. Installeeritud mälu maht kokku: 0 TB. Installitud operatsioonisüsteem: QNAP Turbo System



| Storage | | Performance | |
|--------------------------------------|-------------------------------|-------------------------------------|---|
| Storage drive capacity * | 0 GB | Type * | NAS |
| Storage drive interface * | Serial ATA III | Device class * | Small & Medium Business |
| Supported storage drive interfaces | Serial ATA II, Serial ATA III | Backup function * | ✓ |
| Storage drive sizes supported | 2.5,3.5" | Backup features | Cloud, iSCSI LUN |
| RAID support * | ✓ | Buzzer | ✓ |
| RAID levels | 0, 1, 5, 6, 10, 50, 60, JBOD | Multilingual support | ✓ |
| Online RAID migration | ✓ | Snapshot | ✓ |
| Online RAID expansion | ✓ | Management protocols | SNMP v2/3 |
| RAID rebuild | ✓ | Web-based management | ✓ |
| Hot-swap drive bays | ✓ | Security algorithms | 256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3 |
| Supported file systems | FAT32, HFS+, NTFS, ext3, ext4 | Access Control List (ACL) | ✓ |
| Storage drives installed * | ✗ | Reset button | ✓ |
| Total installed storage capacity * | 0 TB | On/off switch | ✓ |
| Number of storage drives supported * | 8 | Built-in FTP server | ✓ |
| Installed storage drive type * | ✗ | Browser supported | Mozilla Firefox, Microsoft Edge, Google Chrome, Apple Safari |
| Supported storage drive types * | HDD & SSD | System log | ✓ |
| Disk roaming | ✓ | Hot spare | ✓ |
| Processor | | S.M.A.R.T. support | ✓ |
| Processor manufacturer * | Intel | Software | |
| Processor family * | Intel® Celeron® | Operating system installed * | QNAP Turbo System |
| Processor model * | N5095 | Operating system version | 5.0.0 |
| Processor boost frequency | 2.9 GHz | Windows operating systems supported | Windows 10, Windows 11, Windows 7, Windows 8 |
| Processor cores | 4 | Linux operating systems supported | ✓ |
| Processor threads | 4 | Mac operating systems supported | ✓ |
| Number of processors supported | 1 | Server operating systems supported | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 |
| On-board graphics card model | Intel® UHD Graphics | Other operating systems supported | Android, iOS |
| Memory | | Power | |
| Internal memory * | 8 GB | Power supply location | Built-in |
| Internal memory type | DDR4 | Power supply unit (PSU) capacity | 300 W |
| Maximum RAM supported | 16 GB | | |
| Memory slots | 2 | | |
| Memory form factor | SO-DIMM | | |
| Flash memory | 4000 MB | | |

| Network | | Power | |
|---|-------------------------|--------------------------------------|-----------------|
| Ethernet LAN * | ✓ | Number of power supply units | 2 |
| Ethernet LAN data rates | 100,1000,2500 Mbit/s | Redundant power supply (RPS) support | ✓ |
| DHCP server | ✓ | Power consumption (typical) | 55.83 W |
| Jumbo frames support | ✓ | Power consumption (sleep) | 31.742 W |
| iSCSI support | ✓ | AC input voltage | 100 - 240 V |
| Wake-on-LAN ready | ✓ | Fan voltage | 12 V |
| Dynamic DNS (DDNS) | ✓ | Weight & dimensions | |
| Ports & interfaces | | Width * | 482.1 mm |
| USB port * | ✓ | Depth * | 346.4 mm |
| USB 2.0 ports quantity | 2 | Height * | 88.6 mm |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2 | Weight | 7.9 kg |
| HDMI ports quantity | 1 | Package weight | 10.5 kg |
| HDMI version | 1.4b | Packaging content | |
| Ethernet LAN (RJ-45) ports * | 2 | External power adapter | ✗ |
| Concurrent connections | 1500 | Cables included | AC, LAN (RJ-45) |
| Design | | Power cables quantity | 1 |
| Chassis type * | Rack (2U) | Rack mount kit | ✓ |
| Cooling type * | Active | Number of screws | 56 |
| Product colour | Black | Operational conditions | |
| Number of fans | 2 fan(s) | Operating temperature (T-T) | 0 - 40 °C |
| Fan diameter | 8 cm | Operating relative humidity (H-H) | 5 - 95% |
| LED indicators | HDD, LAN, Power, Status | Storage temperature (T-T) | -20 - 70 °C |
| | | Storage relative humidity (H-H) | 5 - 95% |
| | | Logistics data | |
| | | Harmonized System (HS) code | 84714100 |



4711103082188

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-JAN-2025. Prints or copies of Information are only valid on the printed Publication date